



Federal Aviation
Administration



User Manual for Web Frequency Coordination Request - Non-Federal Users

For the

**FAA- Spectrum Engineering Automation System (SEAS)
Support for**

Spectrum Assignment & Engineering Team (AJW-1910)

Contract No. DTFAWA17A-00053

Version 2.5

June 27, 2024

USER MANUAL FOR WEBFCR VERSION 1.2.7

Quality Gate	Name & Title	Date
Update for WebFCR 1.2.1	SEAS Team. OST. Inc.	01/10/2022
Updated with Okta authentication	SEAS Team. Trillion. Inc.	05/02/2022
Updated the Help File version	SEAS Team. Trillion. Inc.	05/23/2022
Updated for WebFCR 1.2.2	SEAS Team. Trillion. Inc.	05/24/2022
Updated for WebFCR 1.2.2	SEAS Team. Trillion. Inc.	06/07/2022
Updated for WebFCR 1.2.3	SEAS Team. Trillion. Inc.	08/04/2022
Updated for WebFCR 1.2.4	SEAS Team. Trillion. Inc.	09/29/2022
Updated for WebFCR 1.2.4.1	SEAS Team. Trillion. Inc.	03/08/2023
Updated for WebFCR 1.2.5	SEAS Team. Trillion. Inc.	08/25/2023
Updated for WebFCR 1.2.6	SEAS Team. Trillion. Inc.	10/26/2023
Updated for WebFCR 1.2.7	SEAS Team. Trillion. Inc.	06/27/2024

CHANGE HISTORY

Number	Date	Section Affected	Change Description / Purpose
1.0	05/14/2015	All	First Draft
1.1	09/01/2015	All	Changes for release 1.1.0
1.2	10/09/2015	All	Updated screenshots
1.3	02/03/2016	All	Changes made for WebFCR 1.1.1
1.4	02/16/2016	Disclaimer	Added screenshot for disclaimer page
1.5	04/22/2016	Cover page	Changes made to WebFCR 1.1.1.2
1.6	06/28/2016	All	Updates/screen shots changed to include all the changes in WebFCR 1.1.1.2
1.7	11/09/2016	All	Added section for status codes
1.8	02/06/2017	All	Change for release 1.1.2
1.9	04/12/2017	All	Revision of Release 1.1.2 content
1.10	08/22/2017	All	Change for release 1.1.3
1.11	10/27/2017	All	Reviewed the format and updated the content
1.12	11/15/2019	All	New/Changed Features in WebFCR 1.1.4
1.13	08/26/2020	Multiple	New/Changed Features in WebFCR 1.1.5
2.0	09/20/2021	All	New Features and change login page
2.1	01/10/2022	All	New Features and Logging Page change
2.2	05/02/2022	Cover & 1.6	New Feature- Okta authentication process
2.2.1	05/23/2022	Cover, All	Updated the version number and screenshots
2.2.2	05/24/2022	All	Final version for WebFCR 1.2.2 release
2.2.3	08/04/2022	All	Final version for WebFCR 1.2.3 release
2.2.4	09/29/2022	All	Final version for WebFCR 1.2.4 release
2.2.5	03/08/2023	All	Final version for WebFCR 1.2.4.1 release
2.3	08/25/2023	Cover & All	Final version for WebFCR 1.2.5 release
2.4	10/26/2023	Cover & 1.16	Final version for WebFCR 1.2.6 release
2.5	06/27/2024	Cover, 1.13 & 1.16	Final version for WebFCR 1.2.7 release

Table of Contents

1.1 Overview of WebFCR.....	6
1.2 FCR Process Overview	6
1.3 Supported Browsers	7
1.4 Disclaimer	7
1.5 Security Warning	7
1.6 Log-In Process.....	9
1.7 FCR Home Page	19
1.8 Dashboard Page.....	21
1.9 Dashboard Page Search Criteria	24
1.10 Dashboard Page Status Codes.....	24
1.11 WebMaster Support	26
1.12 Inquiry Referencing a Specific Assignment	26
1.13 WebFCR New Assignment Submission Using Wizard.....	28
1.13.1 WebFCR New Assignment Submission Using Wizard– Operational	29
1.13.2 New FCR Request Showing Key Service Types Data Request.....	35
1.13.2.1 Service Type – AWOS/ATIS:.....	35
1.13.2.2 Service Type – CLNC DLVY/GBAS/GBTS/LOCAL CTRL/GRND CTRL:.....	40
1.13.2.3 Service Type – Glide Scope (GS):.....	40
1.13.2.4 Service Type – LOC:	41
1.13.2.5 Service Type – VOR/NDB:.....	43
1.13.2.6 Other Service Type	46
1.13.2.7 Additional Information Entry	47
1.13.3 USA/USP Assignment Submission – Operational	50
1.14 WebFCR Modification Assignment Submission – Operational	55
1.15 WebFCR Submitting In Progress Assignment – Operational and Experimental	60
1.16 WebFCR Assignment Submission Using Wizard – Experimental.....	62
1.16.1 WebFCR New Assignment Submission Using Wizard –Experimental	62
1.16.1.1 Functional Use	62
1.16.1.2 Warning/Advisory	63

1.16.1.3 Request Description	63
1.16.1.4 Contractual Reference.....	66
1.16.1.5 Frequency Request.....	68
1.16.1.6 Record Identification.....	75
1.16.1.6.1 General Information.....	76
1.16.1.6.2 Transmitter Information.....	77
1.16.1.6.3 Emission Information	79
1.16.1.6.4 Receiver Information.....	83
1.16.1.6.5 Additional Information.....	84
1.16.2 WebFCR Renewal/Modification Assignment Submission – Experimental.....	84
1.17 Program Implementation Manager (PIM).....	86
1.17.1 PIM Support Areas	87

1.1 Overview of WebFCR

The WebFCR Subsystem is designed to function primarily as a central point of entry for Frequency Coordination Requests (FCRs) from external users via the Internet for both Operational and Experimental requests. The subsystem will route FCRs to the corresponding FAA Staff POCs for further action. The first step requires the proponent to register for a WebFCR account on the system, and as soon as the account is activated the proponent can submit a coordination request. The subsystem's Wizard tool is structured to provide the following capabilities:

- Request new frequency coordination
- Modification of existing frequency assignments which include relocation or update of an approved coordination request
- Allow attachment of pdf files to frequency applications. Obtain status and updates of frequency requests in progress
- Provide feedback and/or request additional information via the Inquiry feature
- Renewal of the existing license, which applies only to the Experimental requests
- For Operational Requests the proponent will work with the FCC to get it renewed
- Dashboards to view the status and manage the submitted frequency requests

1.2 FCR Process Overview

A Frequency Coordination Request (FCR) that is submitted for civil (or military) aviation flight within the NAS is called “An Operational FCR” and it is usually associated with air traffic control operations at an airport. FAA Spectrum also supports FCRs for experimental or testing purposes. In these cases, the FCR is considered “An Experimental FCR”. The general FCR process is:

- To request a frequency coordination for new operational assignments, or experimental assignments is to perform the pre-coordination with FAA (generally before submitting to the FCC for a license). Hence, the user should submit the frequency request via the WebFCR tool, selecting the ‘New application request’ tab, if the required frequency is in or impacts, the Aeronautical bands.
- After the frequency has been reviewed and engineered by the FAA Spectrum engineering team, the proponent typically receives a concurrence or approval from FAA, in conjunction with a coordination number. The proponent is then required to submit to the FCC using the coordination number to validate FAA concurrence. FCC (Federal Communication Commission) will issue the final approval and formal license or authorization to transmit.
- For Modification of an Existing Record. For both Operational and Experimental scenarios: If the proponent is requesting a technical change to an existing assignment, such as new equipment, antenna height update, antenna relocation or transmit power

and/or emissions changes, then the ‘Modification to an Existing License’ tab in the WebFCR tool should be employed to submit the request to FAA Spectrum for reengineering and concurrence.

- For Operational assignments, when a license renewal request is being submitted, and there are no technical changes as listed above, then submit to FAA Spectrum selection the “Renewal” option for coordination.

Note: For all Experimental assignments, license renewal requests both with and without technical changes, must be submitted to FAA Spectrum for coordination before requesting renewal from the FCC.

1.3 Supported Browsers

The following are the browsers that WebFCR supports currently:

1. Chrome 31.0 and above
2. Microsoft Edge
3. Safari 7.0 and above
4. Firefox 31.0 and above

1.4 Disclaimer


Please be advised that there are minimal process variations between assignment processing for Federal and Non-Federal agencies. Hence, the screens may be slightly different for Federal and Non-Federal users.

If you have any question, please contact WebFCR system administrator at

9-AWA-SpectrumCoordination@faa.gov.

1.5 Security Warning

When the WebFCR system is accessed, the system will display a security message as per FAA requirements. This is shown in the image below:



About WebFCR Accept

You are accessing a U.S. Government authorized information system, which includes (1) this computer, (2) this computer network, (3) all computers connected to this network, (4) all devices and storage media attached to this network or to a computer on this network, and (5) all cloud servers and hosting environments supporting this information system. This information system is provided for U.S. Government-authorized use only.


Unauthorized or improper use of this system may result in disciplinary action, as well as civil and criminal penalties.

By logging in and using this information system, you understand and consent to the following:

- You have no reasonable expectation of privacy regarding communications or data transiting or stored on this information system.
- At any time, and for any lawful Government purpose, communication between the user and this information system, data transiting to/from the system, or stored on this system is subject to monitoring, interception, and search.
- Any communications or data transiting or stored on this information system may be disclosed or used for any lawful Government purpose.


Security message of the WebFCR application

The user needs to read and acknowledge the warning message by clicking the ‘Accept’ button on the top right corner. The system displays the WebFCR login page shown below:



← → ↻ 🏠 webforrest.faa.gov/index.aspx

Managed bookmarks FAA Resource Links IT_HELP FAA_Training SEAS APRM WebFCR WebFTA ESVMS

 Federal Aviation
Administration

FAA Home • Offices • Air Traffic Organization • Frequency Coordination Request

WELCOME TO THE FEDERAL AVIATION ADMINISTRATION'S (FAA) FREQUENCY COORDINATION REQUEST (FCR) INTERNET PORTAL

This website allows online filing and processing of radio frequency applications that require FAA coordination.

If you have a requirement to transmit in any of the below frequency bands or if your emissions overlap these frequencies, you are required to coordinate with the FAA:

190-285 kHz	1030 MHz
285-435 kHz	1031-1087 MHz
510-535 kHz	1090 MHz
74.800-75.200 MHz	1094-1150 MHz
108.000-122.6875 MHz	1157-1213 MHz
123.6875-128.8125 MHz	1215-1390 MHz
132.0125-137.000 MHz	2700-2900 MHz
225-400 MHz**	5000-5250 MHz
328.600-335.400 MHz	9000-9200 MHz
978-1020 MHz***	

**Only frequencies in the 225 - 328.575 and in the 335.425 - 399.999 MHz bands that are designated for Air Traffic Control must be coordinated with the FAA. Operation on these frequencies requires a Department of Defense Sponsor and approval of the Military Assignment Group (MAG).

***Frequencies in the band that are going to be used for Link16 (JTIDS) should NOT be coordinated through this website. For Federal applicants of Link16, submit your request directly to NTIA for permanent assignments or coordinate with the Navy Marine Corps Spectrum Center (NMSC) for temporary assignments. For non-Federal applicants, coordinate your request with NMSC through a Department of Defense sponsor.

Access to this website is limited to entities that have a requirement to conduct radio frequency coordination with the FAA. This may include government agencies, the military services, industry.

Login to WebFCR

[Log in](#)

[Register](#)

This is an **UNCLASSIFIED** SYSTEM. Under no circumstances shall classified information be entered and/or uploaded into the WebFCR Portal.

WebFCR Application login page.


1.6 Log-In Process

1. Non-Federal or External Users

An “External User” is a person who is not eligible for a Federal Personal Identity Verification (PIV) credential and requires access via the Internet to WebFCR application. MyAccess Registration requires individuals to verify their identity by providing personal identifiable information (PII) such as a government issued ID or combination of other identifiable attributes such as last 4 digits, home address, and mobile number. Upon successful identity verification, external users will be prompted to complete account registration by establishing a password and a second factor authentication method such as a one-time password sent to a phone or an authentication app.

General Registration process:


- Step 1: Using a Chrome or Edge browser, open URL: <https://webfcr.faa.gov>
- Step 2: The initial web page will be the U.S. Federal System 'Warning' page.
- Step 3: Review and accept via the "Accept" button on the right-hand corner of the banner page.
- Step 4: You will be presented with the WebFCR home page, at this point, please select and click on the 'Register' button, even though you have an active account.
- Step 5: You will then be directed to the Okta Registration page as seen below:




Okta Registration page

The Okta Registration Process:

Step 6: The Okta registration process requests your name and personal email address, followed by a duplicate or dual entry of a password for the Okta account. Okta then verifies this data by sending an email to the given address for verification. The sent message will contain a button to activate and confirm your Okta account.



Followed by the account activation, the registration process requires the setup of a Multifactor Authentication (MFA) and displays the screen as seen below.



Multifactor Authentication (MFA) set-up page

Step 7: At this time it is recommended to use one of the following APP options available via App store/Apple store on the mobile phone:

- a) Google Authenticator
- b) Okta Verify

It is strongly suggested that you download one of these two options, as soon as practical before proceeding further. The instructions listed below are specific to the chosen authentication method.

Google Authenticator

Step 7.1: As noted, first download and Install the Google Authenticator on your phone.

MFA Step 7.1.1: The Okta registration email that has been sent (Step 6) would present a QR Code following the activation of the Okta account, and MFA request.

MFA Step 7.1.2: Open the Google Authenticator App.



MFA Step 7.1.3: Scan the QR code as requested by the authentication process.

MFA Step 7.1.4: The Google Authenticator produces numeric code(s) which should be entered onto your screen.



MFA Step 7.1.5: Enter the authenticator code on the screen to satisfy the validation and click on

Verify button.


MFA Step 7.1.6: Click on Finish button as seen below to complete the authentication process.



Google Authenticator Set-up pages-part 1



Google Authenticator Set-up pages- part 2



Complete Google Authentication page


Okta Verify App Authentication Process

Step 7.2: As noted, first download and Install the Okta Verify App on your mobile phone.

MFA Step 7.2.1: The Okta registration email that has been sent (Step 6) would present a QR Code following the activation of the Okta account, and MFA request.

MFA Step 7.2.2: Open the Okta Authenticator App.

MFA Step 7.2.3: Scan the QR code as requested by the process.



Okta Verify App page – part 1

2:33



myaccessxtl-dev.faa.gov



Setup Okta Verify

Launch Okta Verify on your mobile device and select "Add an account". Scan the QR code to continue.



Can't scan?


Next

Back to factor list


U.S. Department of Transportation



MFA Step 7.2.4: The Okta Verify produces numeric code which should be entered onto your screen, to satisfy the validation and return you to the WebFCR application for full access.



Okta Verify App page – part 3



[FAA Home](#) • [Offices](#) • [Air Traffic Organization](#) • [Frequency Coordination Request](#)

WELCOME TO THE FEDERAL AVIATION ADMINISTRATION'S (FAA) FREQUENCY COORDINATION REQUEST (FCR) INTERNET PORTAL

This website allows online filing and processing of radio frequency applications that require FAA coordination.

If you have a requirement to transmit in any of the below frequency bands or if your emissions overlap these frequencies, you are required to coordinate with the FAA:

190-285 kHz	1030 MHz
285-435 kHz	1031-1067 MHz
510-535 kHz	1090 MHz
74.800-75.200 MHz	1094-1150 MHz
108.000-122.6875 MHz	1157-1213 MHz
123.5875-128.8125 MHz	1215-1390 MHz
132.0125-137.000 MHz	2700-2900 MHz
225-400 MHz**	5000-5250 MHz
328.600-335.400 MHz	9000-9200 MHz
978-1020 MHz***	

***Only frequencies in the 225 - 328.575 and in the 335.425 - 399.999 MHz bands that are designated for Air Traffic Control must be coordinated with the FAA. Operation on these frequencies requires a Department of Defense Sponsor and approval of the Military Assignment Group (MAG).

Login to WebFCR

[Log in](#)


[External User Registration](#)

Our records indicate that your account is pending approval. Please contact your POC for updates.

This is an **UNCLASSIFIED** SYSTEM. Under no circumstances shall classified information be entered and/or uploaded into the WebFCR Portal.

WebFCR Account Pre-Approval page

Upon successful login, the following home page will be displayed with the possible menu options.





WebFCR Application Home page.

2. Support

Please Note:

- (a) In case the user, after creating the account with his or her email in WebFCR application, forgets the password, the 'Forgot Password' link will help to reset the password.

First Time User? Activate or create account
New User? Register for an online account

Verify with your password

@fahelp@faa.gov

Password

Verify

Forgot password?

Help

Back to login

Technical Support:
1 (866) 264-5887 or 1 (866) 527-6948
faahelp@faa.gov

(b) In case the Multi-Function Authentication apps get de-activated and the user is unable to log into via Okta authentication, the user will need to contact the Okta Support using the Help link provided

Sign In - MyAccess

Email address

Sign In

or

Multi-Function Authentication

or

Sign In - MyAccess

or

Forgot password?

Help

Back to login


Technical Support:
1 (866) 264-5887 or 1 (866) 527-6948
faahelp@faa.gov

MyAccess


Sign-In Help

Table of Contents

- Sign-In Help
- Forgot Password
- Multi-Function Authentication
- Sign-In - MyAccess
- Help



Create a case with Okta to resolve



1.7 FCR Home Page

FCR Home page provides information on the WebFCR Portal.

To access this page, click on “FCR Home” link.

The wizard home page provides links and information to review the aviation frequency bands that require prior coordination with the FAA before filing an application with the Federal Communications Commission (FCC). If the users request is not in these bands FAA coordination may not be required.



Federal Aviation Administration

FCR Home Frequency Coordination Request In Progress Dashboard WebMaster Support Help Logout

FAA Home » Offices » Air Traffic Organization » Frequency Coordination Request

WELCOME TO WebFCR For Non-Federal Proponents

What's New

You have accessed the Web Frequency Coordination Request (WebFCR) system for non-Federal proponents. This is the web-based interface that allows non-Federal entities to request and coordinate online the filing, review, and processing of radio frequency applications that require FAA coordination. The FAA is authorized to regulate aviation under Title 49 of the United States Code (USC), Sub-Title VII, Aviation Programs. The Technical Operations Non-Federal Program operates under that authority of FAA Order 6700.20B.

The FAA's Spectrum Assignment and Engineering Group is tasked with protecting all Communication, Navigation, and Surveillance Systems in use throughout the National Airspace System (NAS) from harmful radio frequency interference. For this reason, the FAA has been charged with managing specific frequency bands that are used for aviation. For non-Federal proponents, operation in any of these frequency bands require prior coordination with the FAA when filing an application with the Federal Communications Commission (FCC).

Transmitting in the following frequency bands requires FAA coordination:

190-285 kHz	1030 MHz
285-435 kHz	1031-1087 MHz
510-535 kHz	1090 MHz
74.800-75.200 MHz	1094-1150 MHz
108.000-122.6875 MHz	1157-1213 MHz
123.5875-128.8125 MHz	1215-1390 MHz
132.0125-137.000 MHz	2700-2900 MHz
225-400 MHz**	5000-5250 MHz
328.600-335.400 MHz	9000-9200 MHz
978-1020 MHz***	

**Only frequencies in the 225 - 328.575 and in the 335.425 - 399.999 MHz band that are designated for Air Traffic Control must be coordinated with the FAA. Operation on these frequencies requires a Department of Defense Sponsor and approval of the Military Assignment Group (MAG).

***Frequencies in the band that are going to be used for Link16 (JTIDS) should NOT be coordinated through this website. Please coordinate your request with the Navy Marine Corps Spectrum Center(NMCS) through a Department of Defense sponsor.

The primary purpose of operations in these frequency bands should be for aviation/air traffic control purposes. A Frequency Coordination Request (FCR) that is submitted for this purpose is called "An Operational FCR" and it is usually associated with air traffic control operations at an airport.

On a case by case basis and with a valid justification, the FAA may also support FCRs for experimental or testing purposes. In this case, the FCR is called "An Experimental FCR".

WebFCR landing page for Non Fed proponent

FCR Home page provides the following information.

1. Contact information for any questions on the WebFCR Portal;
2. After hours contact information;
3. Lead time to process coordination requests;
4. Frequencies that requires FAA review and approval;
5. General information on WebFCR – Portal;
6. You may also post any tool related questions through “WebMaster Support”

1.8 Dashboard Page


Federal Aviation Administration

FCR Home
Frequency Coordination Request
Upload Status
Dashboard
WebMaster Support
Help
Logout



+ Search Criteria

(0)	pratyushanofederal@faaseas.com	TRK 193087	11-12-19	USA	USA		RS	11-12-19		?	✖
(0)	pratyushanofederal@faaseas.com	TRK 193058	11-08-19	IAD	DC		PS	11-08-19		?	✖
(0)	pratyushanofederal@faaseas.com	TRK 193025	10-29-19	DC	VA		PS	10-29-19		?	✖
(0)	pratyushanofederal@faaseas.com	TRK 193019	10-28-19	DC	WA		PS	10-28-19		?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182840	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182839	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182838	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182837	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182836	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182835	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(1)	pratyushanofederal@faaseas.com	TRK 182834	07-12-18	GREENVILLE TX			RW	08-08-18	NFEKC07/12/2018(1)	?	✖
(2)	pratyushanofederal@faaseas.com	TRK 182707	08-21-18	GREENVILLE TX			RW	08-08-18	NFEKC08/20/2018(2)	?	✖
(2)	pratyushanofederal@faaseas.com	TRK 182706	08-21-18	GREENVILLE TX			RW	08-08-18	NFEKC08/20/2018(2)	?	✖
(2)	pratyushanofederal@faaseas.com	TRK 182705	08-21-18	GREENVILLE TX			RW	08-08-18	NFEKC08/20/2018(2)	?	✖

Prev 1 2 Next

Export To Excel
Export To CSV

WebFCR Application Dashboard page.

1. The dashboard page can be accessed by clicking on the Dashboard menu.
2. This page displays a set of 10 submitted coordination requests at a time and provides the option to move to the next or previous set.
3. All the fields displayed can be sorted (Ascending and Descending).
4. The data can be exported to an excel format by clicking on the “Export to Excel” button.
5. To sort, click on the column name/headers.
6. If there are any attachments against the coordination request, they are indicated in the
 - a. First column with a paper clip  .
7. Click on paper clip icon to attach additional files (Refer Image A below).
8. Only PDF files less than 10 MB can be attached. Image A on the next page displays the screen to upload.
9. Existing attachments can be downloaded or deleted (Refer Image B below) displays the screen to download/delete attachments.
10. If inquiries need to be raised for a specific assignment, click on the question mark  icon on the far right side of the grid. An inquiry window will open up to raise questions.




Image A – Upload Page.




Image B – Upload Page to View/Delete.

11. An assignment record can be edited or deleted (Withdrawn) using the icons under the “Action” column.

Attach Files	User Email	Tracking Number	Submitted Date	City	State	FAA Coordination No.	FAA Status	FAA Last Updated Date	Project / Exercise	Inquiry	Action
(0)	pratyushanofederal@faaseas.com	TRK 193171	11-19-19	HALF MOON BAY	CA		RS	11-19-19	NFEpn11/19/2019(1)	?	
(0)	pratyushanofederal@faaseas.com	TRK 193169	11-19-19	OWATONNA	MN		PS	11-19-19			
(0)	pratyushanofederal@faaseas.com	TRK 193161	11-18-19	MCLEAN	VA		PS	11-18-19			
(0)	pratyushanofederal@faaseas.com	TRK 193087	11-12-19	USA	USA		RS	11-12-19		?	

Action Column to edit /delete assignments on Dashboard page.

12. To edit an assignment record, click on the pencil  icon.

13. To delete or withdraw an assignment record, click on the red X icon.

14. Assignment records in “Approved” or “Returned without Action” statuses cannot be edited or deleted.


15. Any user within the agency to which the originator of the assignment record belongs can edit an assignment record. However, only the originator of the assignment record will be able to delete an assignment record.

16. If the pencil icon is clicked, “Modification” page opens up populated with all of the information for the associated assignment record. Changes can be made as required and the assignment record can be submitted again.

17. FAA will be automatically notified if an assignment record is edited or deleted.

1.9 Dashboard Page Search Criteria

1. The Search Criteria can be access by clicking on the Dashboard menu.
2. By clicking on search criteria ‘+/- ‘a drop down the window expands or minimize accordingly. User can search for a submitted request assignment by either typing Tracking Number, State, User email, FAA Coordinate No., Submitted data, City, Project exercise, FAA last updated data, FAA status.
3. After entering one required field for the submitted assignment, another row field will appear under the search criteria for this specific assignment.



Federal Aviation Administration

FCR Home Frequency Coordination Request Upload Status **Dashboard** WebMaster Support Help Logout

- Search Criteria

Tracking Number: FAA Coordination No.: Project/Exercise:

User Email: Submitted Date: From To FAA Last Updated Date: From To

State: City: FAA Status:

Attach Files	User Email	Tracking Number	Submitted Date	City	State	FAA Coordination No.	FAA Status	FAA Last Updated Date	Project / Exercise	Inquiry	Action
(0)	pratyushanonfederal@faaseas.com	TRK 193171	11-19-19	HALF MOON BAY	CA		RS	11-19-19	NFEpn11/19/2019(1)		

Prev 1 Next

Search Criteria on Dashboard page.

1.10 Dashboard Page Status Codes

The dashboard page displays different status codes based on the status of assignments. Below is a complete list of the abbreviations of the status codes used on dashboard page.

Status Code	Description
RS	Request Submitted
RA	Request Approved
RW	Request returned without action
AR	Awaiting Response
UR	Request Under Review
PS*	Submitted to PIM
PR*	Returned by PIM

Note: * This status applies only to the Assignment Coordination request for Operational

1.11 WebMaster Support

If there are any specific questions/comments, “WebMaster Support” screen may be used to post those to the System administrator.

This screen can be accessed through main menu WebMaster Support.

Please enter your feedback or any issues related to frequency coordination submission

Subject:

Description:

WebMaster Support on Main menu.

1. Provide a brief text as the Subject or Context of the Inquiry.
2. Use the Description box to provide details and hit “Send E-Mail” when done.

1.12 Inquiry Referencing a Specific Assignment

To check on the status or any other information related to a specific assignment, click on the question mark “?” icon in the dashboard page. Please click [here](#) to view instructions on the dashboard page.

	Tracking No.	Date	Subject	Message Description	User
No data present					
Tracking No.	<input type="text" value="TRK 182876"/>				
Subject	<input type="text" value="Status"/>				
Description	<input type="text"/>				
Message	<input type="text" value="Test"/>				
		<input type="button" value="Send"/>		<input type="button" value="Clear"/>	

View of the Assignment after clicking on Question Mark icon.

	Tracking No.	Date	Subject	Message Description	User
Select	TRK 182837	11/19/2019 11:48:54 AM	Status	PLEASE PROVIDE STATUS	pratyusha nonfederal
Inquiry submitted successfully					
Tracking No.	<input type="text" value="TRK 182837"/>				
Subject	<input type="text"/>				
Description	<input type="text"/>				
Message	<input type="text"/>				
		<input type="button" value="Send"/>		<input type="button" value="Clear"/>	

View of the Submitted assignment request.


1. Upon clicking on the question mark “?” icon on the dashboard page, screen as shown in the screen shot above opens up.
2. Serial number is defaulted.
3. Subject and message information can be typed in.
4. Upon hitting “Send,” the message is sent to FAA personnel responsible for this assignment.
5. When the FAA Spectrum personnel respond back to the inquiry, an E-mail alert will be sent to the requestor.

- This page also serves as a message log and displays all the message communications between the requestor and the FAA Spectrum team.

1.13 WebFCR New Assignment Submission Using Wizard

To create a new coordination request, go to Frequency Coordination Request → New Application Request


This branch of the WebFCR menu takes user to the Data Entry Wizard to allow a structured user friendly series of questions and dropdown lists designed to easily develop the parameters, forms and data inputs for the users given coordination request.



The screenshot shows a web browser window displaying the FAA's WebFCR application. The browser address bar shows the URL: 172.20.7.118/UserInterface/HomeNonFederal.aspx. The application header includes the FAA logo and navigation tabs: FCR Home, Frequency Coordination Request, In Progress, Dashboard, WebMaster Support, Help, and Logout. A dropdown menu is open under 'Frequency Coordination Request', showing options: 'New Application Request' (highlighted), 'Modification to an Existing License', and 'In-progress Application Request'. The main content area features a 'WELCOME TO' message and a 'What's New' section. A table lists frequency bands requiring FAA coordination:

190-285 kHz	1030 MHz
285-435 kHz	1031-1087 MHz
510-535 kHz	1090 MHz
74.800-75.200 MHz	1094-1150 MHz
108.000-122.6875 MHz	1157-1213 MHz

Creating new request.




The screenshot shows a web interface for the Federal Aviation Administration. At the top left is the FAA logo and the text "Federal Aviation Administration". Below this is a dark blue sidebar with a gear icon and the text "Functional Use". The main content area has a light purple header with the text "Functional Use". Below the header is the question "Will this assignment record be used for operational or experimental use?". A red circular icon with a white pencil is centered below the question. A large light purple rectangular box contains two radio buttons: "Experimental Use" (which is selected) and "Operational Use". At the bottom right of the main content area is a dark blue button labeled "Continue".

Functional Use section page.

1.13.1 WebFCR New Assignment Submission Using Wizard– Operational

The user on the FCR wizard home page is recommended to gather technical information about the facility, including the surveyed transmitter antenna latitude and longitude, official airport name, manufacturer's data for transmitter, receiver and antenna equipment, and the proposed aviation service or service type that will be deployed via this request.

The user is provided links with definitions, additional explanation, and key fields with their relative importance and details being requested.



Not secure | 172.20.7.121/UserInterface/Wizard/OperationalUse.aspx

Federal Aviation Administration

WebFCR
FREQUENCY COORDINATION REQUEST

Operational Use

Welcome To The WebFCR Wizard

The FAA's Spectrum Assignment and Engineering Group wizard tool is structured to support the proponent's effort to provide the technical details necessary to submit a non-Federal Frequency Coordination Request to the Federal Aviation Administration (FAA).

The steps necessary to obtain coordination using this Wizard are:

1. Review [Aviation Frequency Bands](#)
2. [Gather technical information](#)
3. Answer at least mandatory questions in Wizard tool
 - [Airport name](#)
 - [Antenna information](#)
 - [Service type](#)
 - [Equipment information and other information if necessary](#)
4. [Submit coordination](#)
5. Check status via Dashboard
6. Confirm coordination completion

Now, the proponent is ready to apply to the FCC for a license.

Back Continue

Operational Use Information WebFCR Wizard page.

FCR Wizard Home page next provides the following information about the submission of the request to the Program Implementation Manager (PIM) sometimes referred to as the non- Federal Program Liaisons.


The FCR application is submitted to the FAA Non-Federal Program Implementation Manager (PIM) who is assigned to review the general request, directly work with the proponent to provide advice, input and initiate the required processes within the FAA to evaluate and facilitate to proponent request. If FCR application changes or revisions are required, the PIM will be able to return the application to the proponent after submission, for the updates and re-submission.

After reviewing the information, click the 'Continue' button to initiate the request by going to Basic Information Page.

The next webpage asks for information about the facility location.

State, City and Airport Name are required fields.

Please enter State, City and Airport Name, and click Continue




The screenshot shows a web browser window with the URL `172.20.7.121/UserInterface/Wizard/BasicInformation.aspx`. The page header includes the Federal Aviation Administration logo and the text "WebFCR FREQUENCY COORDINATION RECORD". A left-hand navigation menu is visible with the following items: "Operational Use", "Basic Info" (highlighted in blue), "Transmitter", "Services/Systems", "Additional Info", and "Summary". The main content area is titled "Specify the State, and actual City, in which the facility is located". It contains three input fields: "State:" with a dropdown menu, "City:" with a text input field, and "Airport Name:" with a text input field. Each field has a red asterisk indicating it is required. At the bottom right of the form area, there are two buttons: "Continue" and "Save & Close".

View of the Basic Information section.

The user should note that, the wizard's left menu allows easy navigation to previous sections and allows the review of a summary of the request. To add technical parameters to any section of the request, it is recommended to navigate via the left menu. At many points throughout the process the user can save the partially completed request.

Another important note is, if the user quits and saves the incomplete application, and returns at a later time, the partially complete application shall be available in the WebFCR under the tab for "upload status page." Upon selection of the incomplete record from the "Upload Status page" the user shall be allowed to complete the application record.

The Transmitter webpage ask the user to specify the transmitter antenna latitude, longitude and antenna height, of which Transmitter Antenna Latitude and Longitude are mandatory fields. The antenna height can be entered in feet or meters, but will be maintained in the reports as feet above ground.



View of the Transmitter Section.

In the next page the specific Service and System Service Type is required.

The FCR Wizard supports many aviation services, and allows the selection of the most likely commercially available productions systems, which might be commonly deployed. The Services available are:

- Automated Terminal Information System
- Automated Weather Observation System
- Clearance Delivery
- Distance Measuring Equipment
- Ground Based Augmentation System
- Ground Based Transmitter System
- Ground Control Outlet
- Ground Control
- Glide Slope
- Localizer
- Local Control
- Non Directional Beacon Outer marker
- Vehicle Squitter
- Very High Frequency Omni Range
- Wide-Area Multi-Lateration

- Inner Marker
- Outer Marker
- Others

The image shows a screenshot of a web form with a dropdown menu open. The form has three required fields: 'Service Type: *', 'Transmitter Type / Model Number: *', and 'Antenna Type: *'. The dropdown menu is currently displaying a list of service types, with 'GROUND BASED AUGMENTATION SYSTEM (GBAS)' selected and highlighted in blue. The list includes: AUTOMATIC TERMINAL INFORMATION SERVICES (ATIS), AUTOMATIC WEATHER OBSERVATION STATIONS (AWOS), CLEARANCE DELIVERY (CLNC DLVY), DATACOMM (VDLM2), DISTANCE MEASURING EQUIPMENT (DME), GLIDE SLOPE (GS), GROUND BASED AUGMENTATION SYSTEM (GBAS), GROUND BASED TRANSMITTER SYSTEM (GBTS), GROUND CONTROL (GRND CTRL), GROUND CONTROL OUTLET (GCO), INNER MARKER (IM), LOCATOR OUTER MARKER (LOM), LOCAL CONTROL (LOCAL CTRL), LOCALIZER (LOC), NON DIRECTIONAL BEACON (NDB), OUTER MARKER (OM), VEHICLE SQUITTER, VERY HIGH FREQUENCY OMNI RANGE (VOR), WIDE-AREA MULTI-LATERATION, and OTHER.

Available Service Type for Operational request

Enter your desired service type, equipment type and antenna type and other information as required then click Continue.

The description for various antenna types can be referred by clicking the “Details” link next to antenna type dropdown. It will open a pop up window with the antenna type description as below:



Antenna Description - Google Chrome
dev-webfcr.faa.gov/UserInterface/Wizard/AntennaDescription.aspx

Service Type	Antenna Description	Antenna Code
Automatic Terminal Information Services (ATIS)	Dipole	DIPOLE
Automatic Terminal Information Services (ATIS)	Dipole Array	DIPOLEARRAY
Automatic Terminal Information Services (ATIS)	Collinear Array	COLLNRARRAY(Gain=4)
Automatic Terminal Information Services (ATIS)	Collinear Array	COLLNRARRAY
Automatic Weather Observation Stations (AWOS)	Dipole	DIPOLE
Automatic Weather Observation Stations (AWOS)	Dipole Array	DIPOLEARRAY
Automatic Weather Observation Stations (AWOS)	Collinear Array	COLLNRARRAY
Automatic Weather Observation Stations (AWOS)	Collinear Array	COLLNRARRAY(Gain=4)
Clearance Delivery (CLNC DLVY)	Collinear Array	COLLNRARRAY
Clearance Delivery (CLNC DLVY)	Dipole Array	DIPOLEARRAY
Clearance Delivery (CLNC DLVY)	Collinear Array	COLLNRARRAY(Gain=4)
Clearance Delivery (CLNC DLVY)	Dipole	DIPOLE
Distance Measuring Equipment (DME)	Collinear Array	DB Systems-DBS5100A-D/7
Distance Measuring Equipment (DME)	Collinear Array	DB Systems-DBS540
Distance Measuring Equipment (DME)	Collinear Array	DB Systems-DBS5100A-D
Distance Measuring Equipment (DME)	Collinear Array	DB Systems-DBS5100A-BD
Distance Measuring Equipment (DME)	Collinear Array	DB Systems-DBS5100A/7
Distance Measuring Equipment (DME)	Collinear Array	DB Systems-DBS5100A
Distance Measuring Equipment (DME)	Collinear Array	FA10153
Distance Measuring Equipment (DME)	Collinear Array	JTP510A
Distance Measuring Equipment (DME)	Collinear Array	DBD510A
Distance Measuring Equipment (DME)	Collinear Array	CA3167
Distance Measuring Equipment (DME)	Collinear Array	FA9783
Distance Measuring Equipment (DME)	Collinear Array	FA8974
Distance Measuring Equipment (DME)	Collinear Array	Wilcox 596
Distance Measuring Equipment (DME)	Collinear Array	Butler 1020
Distance Measuring Equipment (DME)	Collinear Array	FA9639
Ground Based Augmentation System (GBAS)	Dipole Array	TELERAD
Ground Based Augmentation System (GBAS)	Dipole Array	POLAR
Ground Based Transmitter System (GBTS)	Whip	WHIP
Ground Control Outlet (GCO)	Dipole Array	DIPOLEARRAY
Ground Control Outlet (GCO)	Collinear Array	COLLNRARRAY(Gain=4)
Ground Control Outlet (GCO)	Collinear Array	COLLNRARRAY
Ground Control Outlet (GCO)	Dipole	DIPOLE
Ground Control (GRND CTRL)	Collinear Array	COLLNRARRAY(Gain=4)

View of the Pop up Window after Clicking on Details link.

Select the Service Type, Transmitter Type/Model Number and Antenna Type.

Service Type: *	<input type="text" value="DISTANCE MEASURING EQUIPMENT (DME)"/>
Transmitter Type / Model Number: *	<input type="text" value="SECOND GENERATION 9996"/>
Antenna Model: *	<input type="text" value="566"/>
Enter The Antenna Gain	
Antenna Gain:	<input type="text" value="150"/> DBi
Is this DME associated with a Localizer?	
<input type="radio"/> YES <input checked="" type="radio"/> NO	

Service Type / Systems Section.

Please note that based upon the Service Type additional questions and parameters are required. For the DME, NAVAIDS oriented data is required as seen above where the antenna gain and associated runway are requested.

1.13.2 New FCR Request Showing Key Service Types Data Request

1.13.2.1 Service Type – AWOS/ATIS:

For submitting collocated AWOS/ATIS service type:
Click New Application Request → Click Continue → Enter Basic information → Enter location information → Select Service Type AWOS shown below.

Operational Use
Basic Info
Transmitter
Services/Systems
Additional Info
Summary

Select the Service Type, Transmitter Type/Model Number and Antenna Type:

Service Type: * AUTOMATIC TERMINAL INFORMATION SERVICES ▾

Transmitter Type / Model Number: * GENERAL DYNAMICS UHF CM-350 TRANSMITTER ▾

Antenna Type: * DIPOLE ▾ [Details](#)

Enter the maximum Flight Level for this communications service

Maximum Flight Level: 10000 Feet

Is there a collocated AWOS System?

YES NO DON'T KNOW

[Back](#) [Continue](#) [Save & Close](#)


Services/ Systems section for ATIS Service type.

For AWOS and ATIS co-location of the facilities is requested, to support a search for the companion facility.


If the transmitter and receiver are not collocated the user need to provide the latitude, longitude, and if necessary the height for the receiver antenna.

If “Yes,” then the transmitter coordinates and height will be considered for the receiver.

If “No,” the receiver page is opened to enter the receiver information.



Receiver Info is required if not collocated with Transmitter.



Additional Information section.

As shown, the search for an ATIS facility within one NMI (Nautical Mile) of entered coordinates is executed. If a facility identified, it is recorded as True in the additional information section in the next page (Additional Information). Any additional information regarding this coordination request can be entered in the additional information text field in this page along with colocation results. Click continue, summary page is displayed with all the entered field values and related lookup data.

Note: Search for AWOS facility will be performed, similar to above process when the requested facility is ATIS.

Please use the left menu to navigate directly to the section to be revised and enter your corrections.

- Operational Use
- Basic Info
- Transmitter
- Services/Systems
- Additional Info
- Summary

General Information

State:

City:

Airport Name:

Service Type:

Transmitter Information

Equipment Type:

Transmitter Antenna Latitude: Transmitter Antenna Longitude:

Antenna Gain: DBi Antenna Type: Details

Antenna Elevation: Feet Source for Elevation data: USGS Authorized Transmission Radius: NM

Antenna Polarization: Antenna Feed Point Height Above Ground: Feet

Minimum Flight Level: Feet Runway:

Maximum Flight Level: Feet Backcourse:

Voice Option:

View of the summary page before Submission.

Receiver Information

Antenna Latitude: Antenna Longitude:

Antenna Gain: DBi Antenna Type: Details

Antenna Elevation: Feet Source for Elevation data: USGS Antenna Height: Feet

Emission Information

Power: Watts Station Class:

Transmission Bandwidth: kHz Emission Class:

Additional Information


Maximum 1080 characters

Details :

FOR TEST

Summary page before Submission.

After reviewing the information, user can submit or cancel the request by using the appropriate buttons. Click ‘Submit to PIM’, and the coordination request will be submitted to PIM for approval.




Confirmation Message after Submission.

1.13.2.2 Service Type – CLNC DLVY/GBAS/GBTS/LOCAL CTRL/GRND CTRL:

For submitting communications facilities, such as service type CLNC DLVY/GBAS/LOCAL CTRL/GRND CTRL, the receiver information is required

Select Example: Screenshot for Ground Based Transmitter System (GBTS).



Select the Service Type, Transmitter Type/Model Number and Antenna Type:

Service Type: * GROUND BASED TRANSMITTER SYSTEM (GBTS) ▾

Transmitter Type / Model Number: * FREE FLIGHT SYSTEMS FDL-978-TXG/E ▾

Antenna Type: * WHIP ▾ [Details](#)

Back Continue Save & Close

Service Type for Ground Based Transmitter System (GBTS)

1.13.2.3 Service Type – Glide Scope (GS):

For submitting GS service type, a localizer facility is required.

The glideslope cannot be a standalone system. When the GS service type is selected, the system checks the data base for the associated localizer within a two (2) nautical mile radius. If not found, validation message will be displayed as shown below and the ‘Continue’ and ‘Save and Close’ buttons will be disabled so that user cannot proceed with the request. If one or more are found, the glideslope is associated with the localizer.

In your New Application Request → Select Service Type → Glide Slope.

Service Type: * GLIDE SLOPE (GS) ▾

Transmitter Type / Model Number: * GRN 31, MILITARY ▾

Antenna Type: * DIPOLE ARRAY ▾ [Details](#)

Enter The Antenna Gain

Antenna Gain: 700 DBi

Enter the runway number for this navigational aid.

Runway Number: * 22

[Back](#) [Continue](#) [Save & Close](#)

The Glide Slope facility being entered must be paired with a Localizer at the airport. Please enter the Localizer facility prior to entering the associated Glide Slope.

Validation message for GS service type not associated with Localizer.

1.13.2.4 Service Type – LOC:

LOC service type has the transmission radius parameter.

For the New Application Request → Select Service Type → Localizer.

The runway associated with the localizer is required, in addition to the antenna azimuth of the localizer.



Transmitter

Services/Systems

Additional Info

Summary

Service Type: * LOCALIZER (LOC) ▾

Transmitter Type / Model Number: * ASI (FA-10263) LOG PERIODIC ▾

Antenna Type: * LOG PERIODIC ▾ [Details](#)

Number of Elements: * LPD(8E) ▾

Enter the runway number for this navigational aid.
The Runway Number is required to validate the components of the given Instrument Landing System (ILS).

Runway Number: * 23

Azimuth: * 8

Is this a Capture Effect Localizer?

Yes No

Back Continue Save & Close

Services/Systems section for LOC service type.

Receiver Information			
Antenna Latitude:	<input type="text" value="N 38° 57' 27.00"/>	Antenna Longitude:	<input type="text" value="W 077° 26' 49.00"/>
Antenna Gain:	<input type="text" value="15"/> DBi	Antenna Type:	<input type="text" value="Log Periodic"/> Details
Antenna Elevation:	<input type="text" value="276"/> Feet	Antenna Height:	<input type="text" value="21"/> Feet
Source for Elevation data: USGS			

Emission Information			
Power:	<input type="text" value="15"/> Watts	Station Class:	<input type="text" value="ALL"/>
Transmission Bandwidth:	<input type="text" value="2.04"/> kHz	Emission Class:	<input type="text" value="A1A"/>

Additional Information	
Maximum 1080 characters	<input type="text" value="INFORMATION"/>
Details :	

Summary page before Submission.

1.13.2.5 Service Type – VOR/NDB:

VOR/NDB service types have unique ‘Voice’ parameter associated with them. For VOR service type user can select up to two voices from the list and up to one for NDB service type. If no Voice is associated with the request the user can click ‘No’.

Under the New Application Request ->Select Service Type -> Non Directional Beacon.

Select the Service Type, Transmitter Type/Model Number and Antenna Type:

Service Type: *

Transmitter Type / Model Number: *

Antenna Type: * [Details](#)

Is there a Voice?

YES NO

Please select a voice from the List

VISUAL FLIGHT RULES

WEATHER BROADCAST NON-IFR

AUTOMATED WEATHER BROADCAST

AUTOMATIC TRANSCRIBED WEATHER


TRANSCRIBED WEATHER

NDB service type - 'Voice' selection

The Voice Options for a Non Directional Beacon (NDB) are:

Visual Flight Rules	Meaning NDB is for VFR Flight Only
Weather Broadcast non-IFR	Weather Data is meant for VFR Flight
Automated Weather Broadcast	Aviation Weather
Automatic Transcribed Weather	Aviation Weather
Transcribed Weather	Aviation Weather

Similarly, for the selection of Very High Frequency Omni Range (VOR), the system may support the transmission of the weather via a voice signal and the user will be presented the Voice Option question to define the system associated with the VOR voice weather information.



VOR Service Type (user can choose up to two voices).

The Voice Options for a Very High Frequency Omni Range (VOR) are:

RCO Voice
AWOS Weather
ATIS Information
Transcribed Weather
ASOS Weather
Automated Weather Broadcast

1.13.2.6 Other Service Type

If user needs to enter different service type other than listed in Service Type dropdown, they will be given an opportunity to enter their service type by choosing ‘Other’ from the dropdown. In this case, user should provide the following information.

• Service Type	• Antenna Type	• Power
• Transmitter Type	• Frequency	• Modulation
• FCC ID	• Bandwidth	• Type of Information
• Type of Signal		

Service Type: *

Transmitter Type / Model Number: *

FCC ID: *

Antenna Type: * Details

Frequency: * KHz MHz

Bandwidth: * KHz MHz

Power: * Watts

Modulation: *


Type of Signal: *

Type of Information: *

Emission Designator:

Service Type ‘Other’

Emission designator field will be automatically calculated and populated based on the input user provided. Note that all the fields are mandatory in this page. Validation message will be fired for any blank fields or invalid request when user clicks ‘Continue’ button.



Frequency: * KHz MHz

Bandwidth: * KHz MHz

Power: * Watts

Modulation: * ▼

Type of Signal: * ▼

Type of Information: * ▼

Emission Designator:

Please enter/choose the value for Frequency, Bandwidth, Power, Modulation, Type of Signal and Type of Information for this facility.


Validation message for incomplete request

1.13.2.7 Additional Information Entry

Following the “Services and Systems” entry is a free format text entry for additional information.

The purpose of this section is to capture any critical or informative data or comments about the


FCR request and/or facility which might be helpful to the analysis and engineering of the Frequency assignment by FAA Spectrum Engineering and Policy. Please enter this information in the Additional Information Box and/or if there are questions regarding the applicability of any of the information please discuss the situation with the PIM, prior to submittal.



View of the Additional Info. Section,

Once you click continue, the summary page will open with all entered values, lookup values from equipment, and reference tables.

The FCR summary should be reviewed and validated against the official and formally documented information for your facility. Discrepancies should be discussed with the PIM and/or FAA Spectrum to ensure the accuracy of the frequency engineering.



Voice option in the summary page

Receiver Information			
Antenna Latitude:	<input type="text" value="N 38° 57' 27.00"/>	Antenna Longitude:	<input type="text" value="W 077° 26' 49.00"/>
Antenna Gain:	<input type="text" value="0"/> DBi	Antenna Type:	<input type="text" value="Symmetrical Tee"/> Details
Antenna Elevation: <small>Source for Elevation data: USGS</small>	<input type="text" value="276"/> Feet	Antenna Height:	<input type="text" value="21"/> Feet

Emission Information			
Power:	<input type="text" value="25"/> Watts	Station Class:	<input type="text" value="RLB"/>
Transmission Bandwidth:	<input type="text" value="2.04"/> kHz	Emission Class:	<input type="text" value="A2A"/>

Additional Information	
Maximum 1080 characters	<input type="text" value="ADDING ADDITIONAL INFORMATION"/>
Details :	

View of the summary page before Submission.


In order to submit the assignment for review, click submit to PIM. A confirmation page will be displayed with a tracking number, and the record will be submitted to the Program Implementation Manager for review.

Confirmation
Your Frequency Coordination Request is successfully submitted to the Program Implementation Manager (PIM) With Tracking Number TRK 193161
<input type="button" value="Close"/>

View of Confirmation message after Submission.

1.13.3 USA/USP Assignment Submission – Operational

The USA (United States of America) and USP (United States and Puerto Rico) requests are handled differently in WebFCR application. To start the new assignment/request submission process, click Continue button from the Home Page and go to Basic Information Page. Choose USA or USP from state's dropdown.



Specify the State, and actual City, in which the facility is located

State: *
City: *
Airport Name: *

PALMYRA ISLAND
PUERTO RICO
RHODE ISLAND
SOUTH CAROLINA
SOUTH DAKOTA
AMERICAN SAMOA
TENNESSEE
TEXAS
UNITED STATES (50 STATES AND DC)
USA
USP
VIRGINIA
VIRGIN ISLANDS (US)
VERMONT
WASHINGTON

Save & Close

Basic Info. Section for USA/USP request..


State and City are required fields.

Airport Name is optional fields for USA/ USP requests.

Enter at least State and City, and click Continue

For USA/ USP requests, providing Transmitter coordinates is optional.

The transmitter antenna latitude, longitude and antenna height is typical, but for USA-wide records, Transmitter Antenna Latitude and Longitude are not mandatory fields. The antenna height can be entered in feet or meters, but will be maintained in the reports as feet above ground level.




The screenshot shows a web interface for specifying transmitter antenna details. On the left is a dark blue sidebar with a menu containing: Operational Use, Basic Info, Transmitter (highlighted in light blue), Services/Systems, Additional Info, and Summary. The main content area has a title "Specify the transmitter antenna latitude, longitude and height" and a light purple form box. Inside the form box, there are three rows of input fields: "Transmitter Antenna Latitude:" with a text box containing "N 45° 49' 25.99" and a dropdown menu set to "DD°MM'SS.SS"; "Transmitter Antenna Longitude:" with a text box containing "W 038° 42' 25.50" and a dropdown menu set to "DDD°MM'SS.SS"; and "Transmitter Antenna Height (feed point above ground):" with a text box containing "123" and a dropdown menu set to "Feet". Below the form box are three buttons: "Back", "Continue", and "Save & Close".

Transmitter section (USA/USP request).

In the next page the specific Service and System Service Type is not required, Ramp Tester is used in Equipment Type field for test purpose.

The FCR Wizard supports many aviation services, and allows the selection of the most likely commercially available productions systems, which might be commonly deployed. The Services available for USA/ USP requests are:

- **LOC DME**
- **H-ENTR COM**
- **L-ENTR COM**
- **MISC COMN**
- **BEACON**
- **TEST VOR**
- **RAMP TESTER**
- **LOCALIZER**



List of service type for USA/USP requests.

Click Continue → Additional information

In the next page the Frequency field is mandatory, to add more multiple frequencies click on “+ Add more”

Additional Information

Please enter the frequency you want to request

Frequency (In MHz): * [+Add More](#)

Additional Information :

Back

Continue


Save & Close

Additional Info page USA/USP requests.

Click Continue → Summary



Federal Aviation Administration



Operational Use

- Basic Info
- Transmitter
- Services/Systems
- Additional Info
- Summary**

Please use the left menu to navigate directly to the section to be revised and enter your corrections.

1 Frequency requests will be sent for your request of 563 MHz.

General Information

State:

City:

Airport Name:

Service Type:

Frequency (in MHz):

Transmitter Information

Transmitter Type / Model:

Number:

Antenna Model:

Transmitter Antenna Latitude: Transmitter Antenna Longitude:

Antenna Gain: DBI Antenna Type:

Terrain Elevation: Feet
Source for Elevation data: USGS

Antenna Polarization: Antenna Height (feed point above ground): Feet

Minimum Flight Level: Feet Runway:

Maximum Flight Level: Feet Backcourse:

Voice Option:

Receiver Information

Antenna Latitude: Antenna Longitude:

Antenna Gain: DBI Antenna Type:

Terrain Elevation: Feet Antenna Height (feed point above ground): Feet

Frequency Protected Service Volume:

Emission Information

Power: Watts Station Class:


Transmission Bandwidth: kHz Emission Class:

Additional Information

Maximum 1000 characters

INFORMATION

Click Submit to FAA → Confirmation



Confirmation

Your Frequency Coordination Request is successfully submitted.

Tracking Number	Frequency in MHz	State	City
TRK 200211	33	USA	USA
TRK 200212	20	USA	USA
TRK 200213	1	USA	USA


Close

Confirmation message for USA/USP requests

1.14 WebFCR Modification Assignment Submission – Operational

When a given FCC License, impacting the AAG bands, and was previously coordinated with the FAA and requires modification, this process can now be expedited via the WebFCR Wizard.

To submit an assignment for modification request, on the WebFCR main Menu, Click Frequency Coordination Request → Modification to an existing license



Privacy error | Not secure | 172.207.118/UserInterface/HomeNonFederal.aspx

FAA Home | Office | New Application Request | Modification to an Existing License | In progress Application Request

WELCOME TO

You have accessed: Federal prerequisites. This is the web-based interface that allows non-Federal entities to request and coordinate online the filing, review, and processing of radio frequency applications that require FAA coordination. The FAA is authorized to regulate aviation under Title 49 of the United States Code (USC), Sub-Title VII, Aviation Programs. The Technical Operations Non-Federal Program operates under that authority of FAA Order 6700.208.

The FAA's Spectrum Assignment and Engineering Group is tasked with protecting all Communication, Navigation, and Surveillance Systems in use throughout the National Airspace System (NAS) from harmful radio frequency interference. For this reason, the FAA has been charged with managing specific frequency bands that are used for aviation. For non-Federal prerequisites, operation in any of these frequency bands require prior coordination with the FAA when filing an application with the Federal Communications Commission (FCC).

Transmitting in the following frequency bands requires FAA coordination:

190-295 MHz	1030 MHz
285-435 MHz	1031-1087 MHz
510-535 MHz	1090 MHz
74,800-75,200 MHz	1094-1150 MHz
108,000-122,6875 MHz	1157-1213 MHz
123,5875-128,8125 MHz	1215-1390 MHz
132,0125-137,000 MHz	2700-2900 MHz
225-400 MHz**	5000-5250 MHz
328,600-335,400 MHz	9000-9200 MHz
975-1020 MHz***	

**Only frequencies in the 225 - 328.575 and in the 335.425 - 399.999 MHz band that are designated for Air Traffic Control must be coordinated with the FAA. Operation on these frequencies requires a Department of Defense Sponsor and approval of the Military Assignment Group (MAG).

***Frequencies in the band that are going to be used for Linc16 (JTDC) should NOT be coordinated through this website. Please coordinate your request with the Navy Marine Corps Spectrum Center (NMCS) through a Department of Defense sponsor.


The primary purpose of operations in these frequency bands should be for aviation/air traffic control purposes. A Frequency Coordination Request (FCR) that is submitted for this purpose is called "An Operational FCR" and it is usually associated with air traffic control operations at an airport. On a case by case basis and with a valid justification, the FAA may also support FCRs for experimental or testing purposes. In this case, the FCR is called "An Experimental FCR".

The WebFCR interface allows the applicant to:

View of the WebFCR Frequency Modification request.

A search criteria page to perform a search for approved assignments is opened in a new tab on the user's browser. First, the user is asked to enter the call sign or a call sign with the frequency combination. The second option more reliable criteria is entering the transmitter latitude and longitude and/or transmitter latitude and longitude including the frequency combination to search for the record. Third option is Search by state, user can search for a record by selecting a state from a drop down list. When the requested search returns one unique assignment, the details of the assignment will be displayed in the FCR summary form. When the given search returns more than one assignment, the results will be displayed in the grid as shown in the screenshot below.

The user may then click to select his/her desired assignment to open the record for modification in the summary format. The selection could be single or multiple.


Federal Aviation
Administration

Modification to an Existing License

Search By Call Sign

Please use the exact FCC format including spaces

Call Sign: *

OR

Search By Transmitter Antenna Coordinates

Transmitter Antenna Latitude: * DD°MM'SS.SS"

Transmitter Antenna Longitude: * DD°MM'SS.SS"

Frequency


(Optional)

Custom Area Search

USA
 USP
 None

SERIAL	STATE	CITY	FRQ	FATY	LATITUDE	LONGITUDE	STC
<input type="checkbox"/> NG 199971	CA	HALF MOON BAY	1145		N 37° 30' 54.00"	W 122° 22' 44.00"	XC
<input type="checkbox"/> NG 199972	CA	HALF MOON BAY	1046		N 37° 30' 54.00"	W 122° 22' 44.00"	XC

View of the Search Criteria on Modification request.


Federal Aviation Administration

Modification to an Existing License

Search By Call Sign

Please use the exact FCC format including spaces

Call Sign: *

OR

Search By Transmitter Antenna Coordinates

Transmitter Antenna Latitude: * DD°MM'S.S.SS"

Transmitter Antenna Longitude: * DD°MM'S.S.SS"

Frequency MHZ (Optional)

Custom Area Search

USA
 USP
 None


Clear
Submit

☐	SERIAL	STATE	CITY	FRQ	LATITUDE	LONGITUDE	STC
<input type="checkbox"/>	NG 088816	USA	USA	1.1690			ML
<input type="checkbox"/>	NG 088881	USA	USP	5.1384			ML
<input type="checkbox"/>	NG 088882	USA	USP	5.1414			ML
<input type="checkbox"/>	NG 181243	USA	AIRCRAFT	1030			XE


Process

View of the Search Criteria USA/USP on Modification request.

Summary page with multiple record assignments results displayed. The user should accurately identify the target assignment for his renewal process and select accordingly.



Federal Aviation Administration



WebFCR
FREQUENCY COORDINATION REQUEST

Record Identification << 1 of 1 submission(s) >>

General Information Help?

Center Frequency Or Lower Limit:

Upper Limit:

State: * Start Date: End Date:

City: * Hours of Operation:

Function: Length of Daily Transmission: Minutes per Hour

Project: Indoor/Outdoor:

Transmitter Information Help?

Location: *

Coordinates:

Antenna Latitude: * Antenna Height: FEET

Antenna Longitude: * Antenna Gain: dB

Equipment: Antenna Type:

Model Number: Antenna Polarization:

Radius of Operation: KM Antenna Azimuth: Degrees

Flight Level: Min: Feet Max: Feet

PRR (Pulse Repetition Rate): Pulses Per Second Pulse Duration: Milliseconds

Pulse Characteristics (IE Interlace Pattern, Stagger, Jitter, etc):

Emission Information Help?

Emission Designator:

*Emission characteristics:

Bandwidth: * kHz Other Emission characteristics:

Modulation: * Chirp

Type of Signal: * Impulse

Type of Information: * Frequency Hopping

Stopped Interval. If fixed provide interval

Power and System Loss Information:

System Loss: db

Power: * Tx OUTPUT Milliwatts

1030 MHz modes of operation:

Aviation: 3A C S

Military: 1 2 4 5

[View/Update](#) [Save](#) [Add More](#)

Note: Please use the dashboard attachment functionality to upload the Spectrum plot from the Spectrum analyzer showing the emission mask of the transmitter signal and receiver selectivity

Receiver Information Help?

Select if Transmitter and Receiver are in the same location

Coordinates:

Antenna Latitude: Antenna Height: FEET

Antenna Longitude: Antenna Gain: dB

Equipment: Antenna Type:

Model Number: Antenna Polarization:

Radius of Operation: KM Antenna Azimuth: Degrees

[Add More](#)

Additional Information Help?

Purpose of the Request:

Additional Comments:

Contract Information:

Contract Number:

Agency:

NTIA SPS Number:

Agency POC:

J/F-12:

Note: The fields marked * is required entry field, others are optional. But providing the optional fields information will expedite the process

Summary page before submitting experimental requests.

The user should review and update the required fields pursuant to the modification request. If the user wants to submit the assignment for PIM approval following update, click submit to PIM. A confirmation page will be displayed with tracking number. Also, the user wants to cancel the process, click cancel.



View of the confirmation message after submitting.

1.15 WebFCR Submitting In Progress Assignment – Operational and Experimental

Any FCR assignment request that are partially completed and saved and/or previously submitted/rejected by the PIM will be displayed in the users WebFCR In-Progress grid. Click Frequency Coordination Request → In-Progress Application Request to access the In Progress grid.



In-progress Wizard Data

<input type="checkbox"/>	DATE UPLOADED	STATE	CITY	Status	UPDATE
<input type="checkbox"/>	12/9/2019 2:06:13 PM	CA	FERMONT	Operational	In-progress
<input type="checkbox"/>	12/9/2019 1:51:59 PM			Experimental	In-progress
<input type="checkbox"/>	11/20/2019 11:11:37 AM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/20/2019 11:09:18 AM			Experimental	In-progress
<input type="checkbox"/>	11/20/2019 11:07:13 AM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/19/2019 12:15:21 PM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/19/2019 9:21:35 AM			Experimental	In-progress
<input type="checkbox"/>	11/18/2019 2:14:36 PM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/18/2019 2:12:37 PM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/18/2019 10:08:25 AM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/18/2019 8:52:06 AM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/18/2019 8:30:13 AM	VA	MCLEAN	Operational	In-progress
<input type="checkbox"/>	11/12/2019 10:48:47 AM			Experimental	In-progress
<input type="checkbox"/>	11/12/2019 10:28:00 AM			Experimental	In-progress
<input type="checkbox"/>	11/12/2019 8:47:15 AM			Experimental	In-progress
<input type="checkbox"/>	11/11/2019 10:53:12 AM			Experimental	In-progress
<input type="checkbox"/>	11/11/2019 10:48:48 AM	DC	DC	Operational	In-progress
<input type="checkbox"/>	11/7/2019 11:31:26 AM			Experimental	In-progress
<input type="checkbox"/>	10/25/2019 11:51:32 AM			Experimental	In-progress
<input type="checkbox"/>	7/12/2018 7:51:14 PM			Experimental	In-progress
<input type="checkbox"/>	7/12/2018 7:47:19 PM			Experimental	In-progress

Delete Selected

View of the In Progress page.

The assignments under the “In-progress data” show the partially completed assignments. Click on the link “In-progress” to continue working on the assignment.

1.16 WebFCR Assignment Submission Using Wizard – Experimental


This tool is to support **FCR** submission for experimental or testing purposes. When the proponent submits the request via the Wizard, it is routed to the appropriate POC based on the frequency (ies) requested. The FAA spectrum will require minimum 30 days to engineer the frequency, during the processing if there are any questions regarding the coordination request the FAA POC will send the inquiry via the WebFCR inquiry tool. The proponent will review the inquiry and respond to the request for further processing.

The following sections will walk the proponent through the new/relocation/update/renewal request submission process:

1.16.1 WebFCR New Assignment Submission Using Wizard –Experimental

Click Frequency Coordination Request → New Application Request. The Functional Use page should be displayed.

1.16.1.1 Functional Use




View of the Functional Use/ Experimental.

If this assignment record is being used for “Experimental” Select “Experimental Use” and click → Continue. The Warning/Advisory page should be displayed.

1.16.1.2 Warning/Advisory

The page provides the information regarding the pre-requisite necessary for the frequency coordination submission.




View of the Warning Advisory page.

The proponent clicks the continue button, the Request Description Page should be displayed.

1.16.1.3 Request Description

In the Request Description Page, please select the Functions, Station Class, Purpose of the Request and Project Name. Click continue.



The screenshot shows a web browser window with the URL `172.20.7.121/UserInterface/Wizard/RequestDescription.aspx`. The page header includes the Federal Aviation Administration logo and the WebFCR (Frequency Coordination Request) logo. A left-hand navigation menu contains the following items: Functional Use, Warning/Advisory, Description of the Request (highlighted), Contractual Reference, Frequency Request, and Record Identification. The main content area is titled "Frequency Request Description" and contains the following fields:

- Functions:** A dropdown menu with "GROUND PENETRATING RADAR (GPR)" selected. A "Help?" link is visible to the right.
- Station Class:** A dropdown menu with "EXPERIMENTAL RESEARCH STATION (XR)" selected.
- Purpose of the Frequency Request:** A text area containing the word "TESTING".
- Project:** A text field containing "NFEEK01/10/2022(1)".

At the bottom of the form, there are three buttons: "Back", "Continue", and "Save & Close".

View of Description of the Request section.

Functions: Defines the function of the frequency is going to be used for testing.

Data Type: Drop down

Selection Mandatory: Yes

The following options will be presented to the user for selection:

- Ground Penetrating Radar (GPR)
- Synthetic Aperture Radar (SAR)
- Radiolocation
- Antenna Testing
- Simulators
- Unmanned Airborne Systems (UAS)
- Airborne Telemetry
- Radar-based experimental system
- High Intensity Radiation Fields (HIRF)/Personal Electronic Devices(PEDS)
- New radio system development
- IFF/Radar Beacon testing

- Other

Other: when the functions drop down does not have the expected one the proponent is looking for, the proponent should select other. When the “Other” option is selected in Functions drop down, the Other textbox is displayed and mandatory

Other:

Station Class: Station class codes describe the purpose for which a particular station is used. **Data Type:** Drop down
Selection Mandatory: Yes

Listed below are the station class and their definition:

- Experimental Contract Developmental Station - **XC**: An experimental station used for the evaluation or testing under federal government contract of electronics equipment or systems in a design or development stage. (used normally by non-Federal services).
- Experimental Developmental Station - **XD**: An experimental station used for evaluation or testing of electronics equipment or systems in a design or development stage.
- Experimental Export Station - **XE**: An experimental station intended for export and used for the evaluation or testing of electronics equipment or systems in the design or development stage. (used normally by non-Federal services).
- Experimental Composite Station - **XM**: An experimental station used in experimental operations of a complex nature not readily specified or used in an operation which is a composite of two or more of the established experimental categories.
- Experimental Research Station - **XR**: An experimental station used in basic studies concerning scientific investigation looking toward the improvement of the art of radio communications.
- Experimental Testing Station - **XT**: An experimental station used for the evaluation or testing of electronics equipment or systems, including site selection and transmission path surveys, which have been developed for operational use.

Purpose of the request: This field is used to describe the reason for requesting the frequency.

Data Type: Text

Data Length: Up to 250 characters

Project: This name will be associated with the proponent’s request submitted. If there are multiple frequency request submitted at a time, then the project name will aid the proponent to specify the group of submission being referenced by the project name when communicating to the FAA Spectrum POC. This field is editable and the user can customize the project name if needed. The project name is generally defaulted to the format- NFE – (meaning Non-Fed

Experimental), First Name Initial, Last Name Initial, Date (N) (Today's Date) with sequence number for count of submissions today. An Example for User John Doe is:
NFEJD10052017(2).

The system reference placeholder for the project default format is:

“NFEUserFirstNameInitialLastNameInitialDate”.


If there are multiple submissions by the proponent on the same day, the system reference placeholder for the project default format will continue as:

NFEUserFirstNameInitialLastNameInitialDate(n)

Note: Functions, Station Class and Purpose of the Request are *Required entry fields.

When the proponent clicks the continue button, the Contractual Reference Page should be displayed.

1.16.1.4 Contractual Reference




Contractual Reference section.

In the Contractual Reference Page, the following question will be presented to the user ‘Is this request in support of an existing government contract?’

If the user selects ‘No’ then the contractual information fields will not be displayed. The user can select ‘Yes’ if they would like to change their option, otherwise the user clicks ‘Continue’ button to navigate to the frequency request page.

If the user selects ‘Yes’ then the contractual information fields will be displayed. The user is encouraged to enter all of the information fields, if the data is known. Following this entry, click the continue button to proceed to the frequency request page.



View of the Contractual Reference section when selecting “Yes”.

Agency: The agency name for the contract

Data Type: Text

Agency POC: The Contracting Officer (CO/COR) for the contract

Data Type: Text

Contract Number: The Contract number for the contract

Data Type: Text

NTIA SPS Number: Spectrum Planning Sub- Committee (Certification number). This number is typically available and/or can be provided by the Spectrum POC for your agency


Data Type: Text

J/F-12(Spectrum Joint Frequency Equipment Allocation Process): This military equipment reference information is used primarily for frequency coordination request in support of joint U.S military and/or U.S. allied military systems for exercises and testing. The Spectrum POC for your agency will typically be in a position to provide this information

Data Type: Text

The proponent clicks the continue button, the **Frequency Request Page** should be displayed.

1.16.1.5 Frequency Request



Frequency Request [Help?](#)

Specific Frequency | **Frequency Band** | Multiple Frequencies in a Frequency Band | Summary

Please enter specific Frequency and associated Bandwidth in kHz or MHz. Use zero(0) Bandwidth for Continuous Wave.
 Note: One or more specific Frequencies can be added below.

Frequency: kHz MHz Bandwidth: kHz MHz

[Add Frequency to Request](#) [Continue to the next Frequency Option](#) [Summary](#) [Save & Close](#)


[Click here to see the Frequency Bands that require coordination with FAA](#)

Frequency	Bandwidth	Status	Action

View of the Frequency Request section.

Additional enhancements for the 3 special Radar Bands 1215-1390, 2700-2900, and 9000-9200 MHz have been added. These fields only appear when any of the frequency (s) within the 3 special radar bands is selected. The values entered will be displayed in the Record Identification page, and once submitted to FAA, will be added to the Comments and SUP lines in WebAFM as applicable. Below are the screenshots of additional fields for Specific Frequency, Frequency Band, and Multiple Frequencies in a Frequency band option on the Frequency Request page for the 3 radar bands:

Specific Frequency Tab



https://webfcrdev.faa.gov/UserInterface/Wizard/FrequencyOptions.aspx

Federal Aviation Administration

WebFCR
FREQUENCY COORDINATION REQUEST

Frequency Request [Help?](#)

Specific Frequency | **Frequency Band** | Multiple Frequencies in a Frequency Band | Summary

Please enter specific Frequency and associated Bandwidth in kHz or MHz. Use zero(0) Bandwidth for Continuous Wave.
Note: One or more specific Frequencies can be added below. Click Summary Tab to continue.

Frequency: 1215 kHz MHz Bandwidth: 89 kHz MHz

Description of Requirement: (max. 300 characters)
TEST DESCRIPTION OF REQUIREMENTS...

Tuning Range (MHz): 0000.00 to 0000.00


Tuning Increments: 0000.00 MHz

Tuning Limitations: (max. 200 characters)
TEST TUNING LIMITATION

[Add Frequency](#) [Save & Close](#)

[Click here to see the Frequency Bands that require coordination with FAA](#)

Frequency Band Tab



Federal Aviation Administration

WebFCR
FREQUENCY COORDINATION REQUEST

Frequency Request [Help?](#)

Specific Frequency | **Frequency Band** | Multiple Frequencies in a Frequency Band | Summary

Please enter the lower and upper Frequency for the Band(s) in kHz or MHz (**including emissions**).
Note: One or more Frequency Band(s) can be added below. Click Summary Tab to continue.

Lower Frequency: 1215 kHz MHz Upper Frequency: 1299 kHz MHz

Description of Requirement: (max. 300 characters)
FREQUENCY BAND DESCRIPTION OF REQUIREMENTS.

Tuning Range (MHz): 0000.00 to 0000.00


Tuning Increments: 0000.00 MHz

Tuning Limitations: (max. 200 characters)
FREQUENCY BAND TUNING LIMITATION

[Add Frequency Band](#) [Save & Close](#)

[Click here to see the Frequency Bands that require coordination with FAA](#)

Multiple Frequencies in a Frequency Band Tab



Frequency option pages for option 1, option 2, and option 3

Some additional new fields have been included in the Transmitter Information and Emission Information sections on the Record Identification page as show in the screenshots below:

Additional fields/text or text boxes only for the 3 special radar bands are identified with Blue *

Transmitter Information
Help?

Location *

Coordinates

Antenna Latitude *

Antenna Longitude *

Equipment *

Manufacturer:

Model Number:

Is Transmitter mobile? * Yes No

Radius of Operation: KM

Flight Level

Min: Feet

Max: Feet

Antenna Height Above Ground: FEET

Antenna Gain * ? dBi

Antenna Pattern *

Antenna Type * ?

Polarization *

Antenna Orientation * Degrees

Maximum Duty Cycle (%) * ?

Antenna Scan Rate (RPM) * ?

Antenna Tilt Angle * ?

Describe Scan Strategy * ?

Antenna Horizontal -3 dB Beamwidth * ?

Antenna Vertical -3 dB Beamwidth * ?

PRR(s) (Pulse Repetition Rate) * Pulses Per Second

Pulse Duration * Milliseconds

Pulse Characteristics (IE Interlace Pattern, Stagger, Jitter, etc) *

NOTE: PLEASE UPLOAD AS AN ATTACHMENT THE ANTENNA HORIZONTAL AND VERTICAL ANTENNA RADIATION PATTERNS.

Emission Information
Help?

Emission Designator:

*Emission characteristics

Bandwidth * kHz

Note: for Radar please enter -20 dB bandwidth, -3 dB for everything else

Modulation *

Type of Signal *

Type of Information *

Power and System Loss Information:

System Loss: dB

PEAK TRANSMITTER POWER * ? Milliwatts

Other Emission characteristics

Is the pulse chirped? * Yes No

If chirped, the chirped frequency (in MHz):

Bandwidth at each emission point (in MHz) *

-3 dB -40 dB

-20 dB -60 dB

Pulse Rise Time (in Microseconds) * ?

If the system operates over several frequencies or frequency hops, please describe *

Upload Spectrum Plot from Spectrum Analyzer

View/Update Save +ADD MORE EMISSION DESIGNATORS/INFORMATION

Note: Please use the dashboard attachment functionality to upload the Spectrum plot from the Spectrum analyzer showing the emission mask of the transmitter signal and receiver selectively. The development of new aviation-related systems should adhere to requirements based on published standards such as Technical Standard Orders (TSO), International Civil Aviation Organization (ICAO) requirements, RTCA Inc. Minimum Operational Performance Standards (MOPS), and any other applicable standards.



Record Identification Page with changes in different sections

In the Frequency Request Page, the following options are presented to the user to facilitate the entry of the frequencies for FAA Spectrum Coordination:

Note: The proponent should first review carefully the list of aviation frequencies bands listed, against the frequencies or bands being requested including the stated bandwidth to accurately determine the FAA Spectrum coordination impact and overlap. This list can be viewed by clicking the link “[Click here to see the Frequency Bands that require coordination with FAA](#)”.

← → ↻ ⓘ Not secure | 192.168.7.118/UserInterface/Wizard/FrequencyLookUp.html?v=4


Frequency bands that need FAA spectrum coordination	
190-285 kHz	1030 MHz
285-435 kHz	1031-1087 MHz
510-535 kHz	1090 MHz
74.800-75.200 MHz	1094-1150 MHz
108.000-121.9375 MHz	1157-1213 MHz
123.5675-128.6125 MHz	1215-1390 MHz
132.0125-137.000 MHz	2700-2900 MHz
225-400 MHz**	5000-5250 MHz
328.600-335.400 MHz	9000-9200 MHz
978-1020 MHz***	

*Only frequencies in the Annex A of the Military Communications Electronic Board Frequency Plan for 225 - 399.999 MHz should be coordinated with the FAA.

**Frequencies in the band that are going to be used for Link16 should be coordinated with FCC directly.

There are three (3) potential ways to structure a frequency request based on the given requirement:

- **Option #1:** The proponent may use the option to ‘**Request a specific frequency(s)**’ if the specific frequencies are defined for the coordination. Then enter the specific frequency in the text box with the units as KHZ or MHZ. If there are multiple frequencies to request, then the proponent should click the “**Add Frequency to Request**” option to enter the subsequent frequencies. Following, the user is presented the list of the entered requested frequencies with the option to delete, if necessary.



Frequency Request [Help?](#)

Specific Frequency | **Frequency Band** | Multiple Frequencies in a Frequency Band | Summary

Please enter specific Frequency and associated Bandwidth in kHz or MHz. Use zero(0) Bandwidth for Continuous Wave.
Note: One or more specific Frequencies can be added below.

Frequency: kHz MHz Bandwidth: kHz MHz

Add Frequency to Request **Continue to the next Frequency Option** **Summary** **Save & Close**

[Click here to see the Frequency Bands that require coordination with FAA](#)

Frequency	Bandwidth	Status	Action
108 MHz	1 kHz	Needs FAA coordination.	Delete
20 MHz	1 kHz	Outside FAA coordination, Please contact NTIA/FCC directly,	Delete
1111 MHz	1 kHz	Needs FAA coordination.	Delete

Request a specific Frequency.

- **Option #2:** The proponent may use this second option of ‘**Frequency band**’, if the experimental system requires a frequency range. For this option, enter the starting point of the frequency range in the ‘Lower Band’ field in KHZ or MHZ. The ending range in the ‘Upper Band’ field in KHZ or MHZ. If there are multiple frequency bands in the request, then the proponent should click the “**Add Frequency to Request**” option to enter the multiple ranges. Similarly, the user will be presented the list of the entered requested ranges with a delete option as above.

Functional Use
Warning/Advisory
Description of the Request
Contractual Reference
Frequency Request
Record Identification

Frequency Request Help?

Specific Frequency

Frequency Band

Multiple Frequencies in a Frequency Band

Summary

Please enter the lower and upper Frequency for the Band(s) in kHz or MHz (including emissions).

Note: One or more Frequency Band(s) can be added below.

Lower Frequency: kHz MHz Upper Frequency: kHz MHz

Add Frequency to Request
Continue to the next Frequency Option
Summary
Save & Close

[Click here to see the Frequency Bands that require coordination with FAA](#)

Lower Frequency	Upper Frequency	Status	Action
108 MHz	1000 MHz	Needs FAA coordination.	Delete

Request a frequency band.

- **Option #3:** The proponent may use the third option of ‘**Multiple Frequencies in a Frequency Band**’ to be engineered by the FAA when the general frequency range or frequency band is defined. This option is when the specific frequency is not defined, but can be specified within a proposed range of frequencies of defined band. Enter the starting of the frequency range in the ‘Lower Band’ field in KHZ or MHZ, the ending range in the ‘Upper Band’ field in KHZ or MHZ and the number of frequencies to be engineered in the defined range for the experimental device. If the location, emissions and other transmitter characteristics and receiver information are different by assigned frequency, then each request has to be submitted separately.

Functional Use

Warning/Advisory

Description of the Request

Contractual Reference

Frequency Request

Record Identification

Frequency Request Help?

Specific Frequency

Frequency Band

Multiple Frequencies in a Frequency Band

Summary

Please enter the lower and upper Frequency for the Band, the number of specific Frequencies in that Band and the associated Bandwidth in kHz or MHz. Use zero(0) Bandwidth for Continuous Wave.

Note: One or more Frequency Band(s) can be added below. FAA Spectrum will endeavor to engineer the requested number of specific Frequencies within the defined Band, as is possible.

Lower Frequency: kHz MHz Upper Frequency: kHz MHz
 Bandwidth: kHz MHz Number of specific Frequencies:

Add Frequency to Request
Summary
Save & Close

[Click here to see the Frequency Bands that require coordination with FAA](#)

Lower Frequency	Upper Frequency	Bandwidth	Number of Requests	Status	Action
34 MHz	1000 MHz	1 kHz	3	Needs FAA coordination.	Delete

Request multiple frequencies.

Note: Multiple frequencies can be requested by clicking the Add Frequency to Request and the selected frequencies will be displayed in the table ‘Frequency Selected’. Each frequency selected will have a delete button next to it, for the proponent to cancel the requested frequency.

Please provide any additional information to clarify: This text field is presented to the proponent to enter any notes and details that will help FAA Spectrum in engineering the frequencies.

The proponent clicks the continue button, the **Record Identification** Page should be displayed.

1.16.1.6 Record Identification

Note: If the proponent enters multiples for the specific frequencies or frequency bands (**Option #1 or #2**), multiple records will be created, hence, the record identification page will be displayed multiple times, presenting a record identification page for each frequency or band requested. In this mode, the proponent is allowed to update the fields as necessary for each request. After confirmation by the proponent, a tracking number will be generated for each request and each will be submitted to the FAA Spectrum for further processing.

If the proponent request requires a number of frequencies, “Pursuant to FAA engineering” (**Option #3**), then the record identification page will be displayed only one time and will again allow the user update the fields for the request. After confirmation by the proponent, the tracking number will be generated based on the number of frequencies entered by the proponent. The request will be submitted to the FAA Spectrum for further processing. All the parameters selected for the group will be applied to each of the individual requests.

The status of the request can be viewed in the dashboard, refer to section [1.6 Dashboard](#), for specifics on accessing dashboard information

The record identification page will be the summary page of the information entered by the proponent for description of the request, contractual reference and frequency request page

The page is divided into four sections: **General Information; Transmitter Information, Emitter Information and Receiver Information.**

1.16.1.6.1 General Information

The **Generation Information** section has the following fields:

- **Center Frequency or Lower Limit:** The frequency selected in the option 1 or lower band entered in Option 2 or 3 in the frequency request page is populated.
- **Upper limit:** The frequency upper band entered in Option 2 or 3 in the frequency request page is populated.
- **State:** Select the state in which the site of the transmitting station is located.
- **City:** Enter the name of the city or other geographical subdivision in which the site of the transmitting antenna is physically located.
- **Function:** The value will be populated that was selected in the “Request Description Page.”
- **Project:** The value will be populated that was selected in the “Request Description Page.”
- **Start Date:** The start date for the frequency requested to be used temporary frequency request, this can be selected using a date picker. It cannot be selected less than the current system date.
- **End Date:** The end date for the frequency requested to be used for a temporary frequency request, this can be selected using a date picker.

For temporary frequency request the end date is mandatory.

Hours of Operation: Denotes the time frame, when the frequency will be used and should be entered in the format M-F/9AM -5 PM.

Length of Daily Transmission: Indicates the duration the frequency will be used for transmission, select the unit as Seconds, minutes or Hours and enter the number in the text field.

Indoor/Outdoor: Select Indoor or Outdoor to indicate where the location of the antenna will be used for transmission.

1.16.1.6.2 Transmitter Information

The **Transmitter Information section** has the following fields:

1. ***Location:** Drop down: The proponent selects the Airborne/Ground/Both to indicate the location of the transmitter values: Airborne; Ground; Both.

Note: The Location selection is mandatory.

When the proponent selects “both,” the record identification page will be displayed twice; once for the airborne request and once for the ground request. The record identification page should first display the Airborne parameters (Antenna Height field should be disabled) notifying the user that the data input request is for Airborne and then clear the data to display the Ground parameters (flight level and Antenna Height field should be displayed) with a heading asking the user to input the Ground related information. The coordination will be considered as two records. The label above the Location field will indicate which type of location is requested to be entered by the user.

2. ***Coordinates:**

Antenna Latitude: Proponent inserts two characters each for the degrees, minutes, and seconds of the latitude of the site named in the transmitter antenna location

Antenna Longitude: Proponent inserts in degrees (3 characters), minutes (2 characters) and seconds (2 characters), the longitude of the site named in the transmitter antenna location. **Note:** The coordinates entry is mandatory

3. **Radius of Operation:** Enter the radius of operation from a given geographical location actions,

Data Type: *Text field:*

Units Drop down box: *values:* KM (Kilometer); NMI (Nautical Miles)

4. **Equipment:**

Manufacturer: Select the Manufacturer of the antenna for which you are requesting the frequency coordination from the manufacturer drop down. If the Manufacturer that you are looking for is not available, then select the Other Option. In the textbox “**Other**” enter the name of the Manufacturer and in the “please justify” textbox enter the justification.

Model Number: Enter the model number of the Antenna in the Model Number. **Data Type:** *Text field*

5. **Flight Level:**

Min: Minimum altitude

Max: Maximum

altitude **Data Type:**

Text field

Unit: Feet

6. **PRR (Pulse Repetition Rate):** Enter the pulse repetition rate for the application. If for an assignment using a secondary radar on the frequency 1030 MHz or for pulsed radars operating in the bands 1215-1400, 2700-2900, and 9000-9200 MHz, for example.

(The pulse repetition rate is typical for 1030M and pulsed assignments, particularly those in the radar bands).

Data Type: Text Field; Enter multiple values with the '/' delimiter, the range should be entered like 1-20

Units: pulses per second

Examples: 320.1.3K

Note: If the value is above 999 PPS and in thousands at 1000 PPS and above, it is required to add the letter K at the end of the numeric value

7. **Pulse Duration:** Value indicates the characteristic pulse duration(s) of the equipment.

Data Type: Text field; Enter multiple values with the '/' delimiter, the range should be entered like 1-20

Unit drop down values – micro seconds and milli seconds

8. **Pulse Characteristics (IE Interlace Pattern, Stagger, Jitter, etc.):** **Data Type:** Text field (max character limit is 500)

9. **Antenna Height:** Feed point Above ground:

Data Type: Text field;

Units drop down values: meters; feet

10. **Antenna Gain:**

Data Type: Text field;

Unit: dB

11. **Antenna Type:**

Data Type: Dropdown box

12. **Antenna Polarization:** Transmitter antenna polarization. **Data Type:** Drop down box
Select one of the following values based on the antenna type:

- D-Rotating
- E-Elliptical
- H- Horizontal
- J--Linear
- L--Left Hand Circular
- R--Right Hand Circular
- S--Horizontal and Vertical
- T--Right and Left Hand Circular
- V--Vertical
- X--Other

Note: Mandatory for transmitting earth or terrestrial stations (including experimental stations) employing Earth station techniques; or for transmitting Space or Terrestrial stations (including experimental stations) using space station techniques.

13. **Antenna Azimuth:** Transmitter Antenna Orientation

Data Type: *Text field;*

Units drop down values: *degrees or omnidirectional*

Note: Mandatory to provide the value only if the antenna is steerable or directional. If the antenna is omnidirectional or rotating it is not required.

1.16.1.6.3 Emission Information

Emission characteristics:

1. ***Bandwidth:** Necessary bandwidth

Data Type: *Text Field;*

Units: *HZ; KHZ; MHZ*

2. ***Modulation:** Indicates the type of modulation of the main carrier

Data Type: **drop down box**

A	Double-sideband	Amplitude Modulated
B	Independent sidebands	
C	Vestigial sideband	
H	Single-sideband, full carrier	
J	Single-sideband, suppressed carrier	
R	Single-sideband, reduced or variable level	
F	carrierFrequency modulation	Angle Modulated
G	Phase modulation	

D	Emission in which the main carrier is	Amplitude and Angle
P	amplitudeSequence of unmodulated pulses.- modulated and angle-modulated	Pulse
K	Modulated in amplitude	
L	Modulated in width	
M	Modulated in position	
Q	angle-modulated during the period of the	Frequency or Phase
V	pulseA combination of the foregoing or produced	
W	by other meansCases not covered above, in which an	Combination
X	emisCases not otherwise covered.ion consists of the main carrier	Explained in Supplementary Details (SUP)
N	Emission of an unmodulated carrier.	

3. ***Type of Signal:** Indicates the details of the signal

Data Type: drop down box

Symbol	Type of Emission
0	No modulating signal.
1	A single channel containing quantized or digital signals without the use of a modulating subcarrier. (This excludes time-division multiplex.)
2	A single channel containing a quantized or a digital signal with the use of modulating subcarrier.
3	A single channel containing an analogue signal.
7	Two or more channels containing quantized or digital signals.
8	Two or more channels containing analogue signals.
9	A composite system with one or more channels containing quantized or digital signals, together with one or more channels containing analogue signals.
X	Cases not otherwise covered. Explained in Supplementary Details (SUP)

4. ***Type of Information:** Indicates the type of information to be transmitted *Data Type: drop down box*

Symbol	Type of Emission
N	No information transmitted.
A	Telegraphy--for aural reception.
B	Telegraphy--for automatic reception.
C	Facsimile.

D	Data transmission, telemetry, telecomm and; (the symbol D indicates that data, telemetry, or telecomm and information is being transmitted individually or, that any combination of the three are being transmitted simultaneously. If any combination is being transmitted simultaneously, one of the multichannel symbols, 7, 8, or 9, must be used for the second symbol.)
E	Telephony (including sound broadcasting).
F	Television (video).
W	Combination of the above. (Use only for multi-channel systems having the capability of transmitting all information simultaneously).
X	Cases not otherwise covered. Explained in Supplementary Details (SUP)

5. System Loss:

Data Type: Text field

Units: dB

6. ***Power:** This field is for the transmitter output power NORMALLY supplied to the antenna transmission line. The power can be entered as output or ERP (ERP stands for effective radiated power)

First Drop down values will be Transmitter output and ERP: Select the type

Data Type Text Field: Enter the output power or ERP

TX Output Units: Dropdown box: values: Milliwatts; watts; KWatts; MWatts

ERP Units: Dropdown box: values: dBm;dBW

Note: The following conversions are performed by the tool, this is for informational purpose and there is no action from the proponent end.

When the power is selected output there will be no conversion applied. If the power is entered in ERP, the following calculation will be performed

ERP power in dBm or dBW – system loss +gain

The value obtained from above formula will be converted to watts using the following conversion

If ERP was entered in dbm

$$\text{Power in w} = 10^{((P(\text{dBm}) - 30) / 10)}$$

If ERP was entered in dBW

$$\text{Power in W} = 10^{\frac{\text{Power in dBW}}{10}}$$

7. Other Emission characteristics:

Chirp: Checkbox format
Impulse: Checkbox format
Frequency Hopping: Checkbox format
Stepped Interval. If Fixed provide interval: Text field

Note: The value is required only if

8. 1030 MHz modes of operation:

Checkboxes for each option:


Aviation: 3A; C; S

Military: 1; 2; 4 ;5


Multiple values can be selected.

There should be a [+ Add More](#) hyperlink provided below this section

Note: **Please use the [dashboard attachment](#) functionality to upload the Spectrum plot from the Spectrum analyzer showing the emission mask of the transmitter signal and receiver selectivity**



Transmitter spectrum plot from a spectrum analyzer showing the spectrum mask



Spectrum Plot of the IF Receiver Selectivity/Independent Frequency Rejection (IFR)

1.16.1.6.4 Receiver Information

The following option should be provided with a checkbox to the user below these fields: Select if Transmitter and Receiver are in the same location (Checkbox). If the Transmitter and Receiver are located in the same location, when the proponent select this checkbox then the transmitter information will be copied to the receiver. If the receiver and transmitter are not located in the same location, the selection of the checkbox is not required and the parameters for the receiver should be entered by the proponent

If the Transmitter and Receiver are not located in the same location, then the proponent will not select the checkbox and enter the receiver information 1. Coordinates: Antenna Latitude:

Antenna Longitude:

2. (Default Format) Degrees, Minutes, Seconds with 2 digit decimals; [indicate options] [provide tool tips]
3. Equipment: Manufacturer: Dropdown box; values refer to Manufacturer table
 - i. Model Number: Text Field
 - ii. Other: [Display this statement "Please contact NTIA to get the equipment approved"]
4. Radius of Operation: Text field unit Dropdown box values: KM or Nautical miles
5. Antenna Height: Above ground: Text field unit Dropdown box values: Meters or Feet
6. Antenna Gain text field unit - dB
7. Antenna Type: Dropdown box (If the antenna type is an array, then the gain should not be populated and the proponent will enter the value).

8. Antenna Polarization Dropdown box
9. Antenna Azimuth: text field; units drop down values: degrees or omnidirectional.

There should be a “[+Add more](#)” hyperlink provided below this text field.

1.16.1.6.5 Additional Information

1. Purpose of the Request; Text field; populated from the Request Description page.
2. Additional comments: Text field (max character limit is 1080). The field will be prepopulated information if the proponent enters in the ‘Please provide additional information to clarify’ should be prepopulated and the field should be editable.
3. Contract Information: auto populated if the user entered details in the Contractual Reference page.
4. Contract Number: Text field; auto populated if the user entered details in the Contractual Reference page.
5. Agency: Text field; auto populated if the user entered details in the Contractual Reference page.
6. NTIA SPS Number: Text field; auto populated if the user entered details in the Contractual Reference page.
7. Agency POC: Text field; auto populated if the user entered details in the Contractual Reference page.
8. J/F-12: Text field; auto populated if the user entered details in the Contractual Reference page.


Click the submit button and the request form gets submitted to FAA Spectrum. An email notification will be sent to the proponent with the tracking number. The proponent should allow 30 days from the day of submission for FAA Spectrum Engineering to process the record.

If you have reached 30 days and did not receive any communications, the proponent may use the inquiry feature available in the tool to communicate to the FAA Spectrum POC.

1.16.2 WebFCR Renewal/Modification Assignment Submission – Experimental

When a given FCC License, which impacts the AAG bands, and was previously coordinated with the FAA is subsequently scheduled for renewal/modification, this process can now be expedited via the WebFCR Wizard.

To submit an assignment for renewal/modification request, on the WebFCR main Menu, click “Frequency Coordination Request” → “Modification to an existing license.”



Federal Aviation Administration

FCR Home | **Frequency Coordination Request** | Upload Status | Dashboard | WebMaster Support | Help | Logout

FAA Home • Office

- New Application Request
- Modification to an Existing License
- In-progress Application Request

WELCOME TO
For Non-Federal

You have accessed the Web Frequency Coordination Request (WebFCR) system for non-Federal proponents. This is the web-based interface that allows non-Federal entities to request and coordinate online the filing, review, and processing of radio frequency applications that require FAA coordination. The FAA is authorized to regulate aviation under Title 49 of the United States Code (USC), Sub-Title VII, Aviation Programs. The Technical Operations Non-Federal Program operates under that authority of FAA Order 6700.20B.

The FAA's Spectrum Assignment and Engineering Group is tasked with protecting all Communication, Navigation, and Surveillance Systems in use throughout the National Airspace System (NAS) from harmful radio frequency interference. For this reason, the FAA has been charged with managing specific frequency bands that are used for aviation. For non-Federal proponents, operation in any of these frequency bands require prior coordination with the FAA when filing an application with the Federal Communications Commission (FCC).


Transmitting in the following frequency bands requires FAA coordination:

190-285 kHz	1030 MHz
285-435 kHz	1031-1087 MHz
510-535 kHz	1090 MHz
74.800-75.200 MHz	1094-1150 MHz
108.000-121.9375 MHz	1157-1213 MHz
123.5875-128.8125 MHz	1215-1390 MHz
132.0125-137.000 MHz	2700-2900 MHz
225-400 MHz**	5000-5250 MHz
328.600-335.400 MHz	9000-9200 MHz
978-1020 MHz***	

Home Page -Modification to existing License.

The search criteria page to perform a search for approved assignments will open in a new tab on the user's browser. The user is asked to enter the call sign or a call sign with the frequency combination. The third, more reliable entry criteria would be entering the Transmitter Latitude and Longitude and/or Transmitter Latitude and Longitude including the Frequency combination to search for the record. When the requested search returns one unique assignment, the details of the assignment will be displayed in the FCR record summary form. When the given search returns more than one assignment, the results will be displayed in the grid as shown in the screenshot below.

The user may then click to select his desired assignment to open the record for renewal in the record summary format. The user should accurately identify the target assignment for his/her renewal process and select accordingly.



Modification to an Existing License

Search By Call Sign
Please use the exact FCC format including spaces
Call Sign: *

OR

Search By Transmitter Antenna Coordinates
Transmitter Antenna Latitude: * DD°MM'S.S.S\"/>
Transmitter Antenna Longitude: * DD°MM'S.S.S\""/>

OR

Search By State
Please choose state from below
State:

Frequency (optional) MHz

SERIAL	STATE/CITY	FRQ	FATY LATITUDE	LONGITUDE	STC
<input type="checkbox"/>	CA HALF MOON BAY	1145	N 37° 30' 54.00"	W 122° 22' 44.00"	XC
<input type="checkbox"/>	CA HALF MOON BAY	1048	N 37° 30' 54.00"	W 122° 22' 44.00"	XC

Modification to existing License.

The user can select single assignment or multiple by selecting the checkbox next to the assignments and clicks the process button. Each will be processed in order. The following record identification page will display the details of the assignment.

For renewal request without NO modifications, the proponent should click the “Submit to FAA Spectrum” button. If the proponent would like to submit modifications to the request, the technical changes and updates would be made in the form; and click the “Submit to FAA Spectrum” for processing.

A confirmation page will be displayed with tracking number. Also, the user wants to cancel the process, click “Cancel.”


1.17 Program Implementation Manager (PIM)

The Program Implementation Manager (PIM), sometimes referred to as the Non-Federal Program Liaisons, and/or Non-Federal Coordinators, have access within WebFCR to review via a Service Area focused dashboard to see all new assignments submitted by the proponent(s) for their given service area. The PIM typically is NOT involved in the license renewal process. After login, the Service Area PIM user is displayed the PIM Home page which has information for the PIM summarizing the FCR review process and suggested support which may be applicable.

The general objective of this interim PIM validation process is to allow the PIM to confirm from the Proponent the given criteria and basis for his FCR application and to provide a determination that FAA intends to proceed with the new facility as a project. In addition, the PIM is to initiate the key FAA process steps required to support the proponent’s FCR request pursuant to FAA requirements.

1.17.1 PIM Support Areas

- 1) "Review the submitted data on the basic frequency coordination summary and confirm the validity of the application and next steps.
- 2) "Confirm the latitude and longitude of the transmitter antenna as indeed official survey data, and that the antenna height is the distance from the ground to the antenna feed point.
- 3) "For new facilities, coordinate with NFDC to obtain the FAA Identification Code for the transmitter facility and add it to the application.
- 4) Review the purpose, related data and parameters are generally sufficient for Spectrum to proceed with engineering the frequency assignment.
- 5) Upon agreement with the proponent, send the application to FAA Spectrum to schedule the engineering of the Frequency Coordination Request (FCR).



Federal Aviation Administration

FCR Home Frequency Coordination Request Upload Status Dashboard WebMaster Support Help Logout

FAA Home > Offices > Air Traffic Organization > Frequency Coordination Request

Welcome To The WebFCR Non-Federal Program Implementation Manager (PIM) Tool What's New

The FAA's Spectrum Assignment and Engineering Group (Spectrum) has structured this Tool to support the PIM in the review and validation of non-experimental Frequency Coordination Requests (FCR) filled by non-Federal proponents.

The PIM's review and validation process includes the following:

- For new facilities, verify that the FCR application is valid for the location and aeronautical service requested.
- For new facilities, coordinate with the National Flight Data Center group to obtain the FAA Identification Code for the new facility. Include this information in the FCR application before submitting it to Spectrum.
- For new facilities and relocation of existing facilities, verify that the latitude and longitude of the transmitter antenna in the FCR application is actual surveyed data.
- For all applications, verify that the antenna height in the FCR application is the actual distance from the ground to the antenna feed-point.
- For renewal request, verify that the existing Federal Communications Commission (FCC) license is still valid.

Note that for renewal requests, a coordination is only necessary if there is a technical change in the application, such as new equipment, revised latitude/longitude, etc.


Once the review and validation process is completed, the PIM submits the FCR application to Spectrum.

For reference, the frequency bands that require prior coordination with the FAA before filing an application with the FCC are detailed on the WebFCR Login page.

WebFCR home page for PIM user.

Following the summary PIM Home page, the primary action Tab available is the FCR Dashboard. Upon Clicking on the Dashboard tab, the user is displayed a view the proponent(s) assignments submitted for the respective service area.

The Dashboard displays all submitted assignments from both new and renewal application request. Also, those assignments which may have been previously returned to a proponent for revision are displayed.



The screenshot shows the FCR Dashboard interface. At the top, there is a navigation bar with the following tabs: FCR Home, Frequency Coordination Request, Upload Status, **Dashboard**, WebMaster Support, Help, and Logout. Below the navigation bar is a search criteria section. The main content area displays a table with the following columns: Attach Files, User Email, Agency Serial No., Submitted Date, City, State, FAA Coordination No., Frequency in MHz, FAA Status, FAA Last Updated Date, Project / Exercise, and Action. The table contains 15 rows of data, each representing an assignment. Below the table, there are two buttons: "Export To Excel" and "Export To CSV".

Attach Files	User Email	Agency Serial No.	Submitted Date	City	State	FAA Coordination No.	Frequency in MHz	FAA Status	FAA Last Updated Date	Project / Exercise	Action
(0)	ip_nonfederaluser@faaseas.com	TRK 193167	11-18-19	HERNDON	VA		118	PS	11-18-19		[Action]
(0)	pratyushanonfederal@faaseas.com	TRK 193161	11-18-19	MCLEAN	VA		0.19	PS	11-18-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193154	11-18-19	HERNDON	VA		980	RS	11-18-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193147	11-15-19	HERNDON	VA		118	PS	11-15-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193141	11-14-19	HERNDON	VA		118	RS	11-14-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193109	11-13-19	HERNDON	VA		118	RS	11-13-19		[Action]
(0)	pratyushanonfederal@faaseas.com	TRK 193058	11-06-19	IAD	DC		118	PS	11-06-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193036	10-31-19	HERNDON	VA		118	PS	10-31-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193027	10-29-19	HERNDON	VA		118	PS	10-29-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193026	10-29-19	HERNDON	VA		118	PS	10-29-19		[Action]
(0)	pratyushanonfederal@faaseas.com	TRK 193025	10-29-19	DC	VA		118	PS	10-29-19		[Action]
(0)	ip_nonfederaluser@faaseas.com	TRK 193024	10-29-19	HERNDON	VA		118	PS	10-29-19		[Action]

View of the Dashboard page for PIM user.

On the PIM Dashboard the FAA Status Codes are:

FAA Status	Description PS
Submitted	Proponent
PR	Returned to Proponent
RN	Region New (FAA Spectrum)

The Action button, allows the PIM user to review and approve/reject an assignment. A summary window is opened which displays the given assignment information. PIM can only process only the assignments with FAA status as PS. Those with FAA Status PR have been returned to the proponent for revision and re-submission.

Non-Fed Proposal Summary
Close

Serial Number: Frequency: MHz

General Information

IDENT:

State:

City:

Airport Name:

Service Type:

Transmitter Information

Non-Fed Proposal Summary
Close

Transmitter Information

Equipment Type:

Transmitter Antenna Latitude: Transmitter Antenna Longitude:

Antenna Gain: DBi Antenna Type: [Details](#)

Antenna Elevation: Feet Authorized Transmission Radius: NM
Source for Elevation data: USGS

Antenna Polarization: Antenna Feed Point Height Above Ground: Feet

Minimum Flight Level: Feet Runway:

Maximum Flight Level: Feet Backcourse:

Voice Option: Azimuth: °

Receiver Information

Antenna Latitude: Antenna Longitude:

Antenna Gain: DBi Antenna Type: [Details](#)

Antenna Elevation: Feet Antenna Height: Feet
Source for Elevation data: USGS

Non-Fed Proposal Summary
Close

Receiver Information

Antenna Latitude: <input type="text" value="N 32° 57' 46.00"/>	Antenna Longitude: <input type="text" value="W 082° 49' 57.00"/>
Antenna Gain: <input type="text" value="0"/> DBi	Antenna Type: <input type="text" value="Dipole"/> Details
Antenna Elevation: <input type="text" value="431"/> Feet <small>Source for Elevation data: USGS</small>	Antenna Height: <input type="text" value="15"/> Feet

Emission Information

Power: <input type="text" value="10"/> Watts	Station Class: <input type="text" value="FAB"/>
Transmission Bandwidth: <input type="text" value="6"/> kHz	Emission Class: <input type="text" value="A3E"/>

Additional Information

Details:

REQUESTING NG T AND VHF FREQUENCY TO PROCEED WITH FCC VHF FILINGS.RADIO WILL BROADCAST AT MAX 2.5 WATTS

Proponent Information:

TRACKING NUMBER: TRK 190585, REQUESTOR INFORMATION: TRENT SANDERS, TSANDERS@DBTTTRANSERV.COM, 812-805-5558.

View of the summary for assignment information.

As outlined earlier, the PIM is encouraged to communicate with the proponent, to review the submitted FCR request and to provide the support and clarifications which may be required by the proponent.

Following the review and support is provided, the PIM can concur with the FCR request by clicking on the “Submit to FAA Spectrum” Button.

To return the assignment to proponent for any revision or update, upon clicking Return to Proponent for Revision and a text box will open, allowing the PIM user to enter the reason for return/update and then click “Return to Proponent for Revision” again. Once returned, the FAA status of the assignment will be updated to PR.

Non-Fed Proposal Summary Close

Power:	<input type="text" value="10"/>	Watts	Station Class:	<input type="text" value="FAB"/>
Transmission Bandwidth:	<input type="text" value="8"/>	kHz	Emission Class:	<input type="text" value="A3E"/>

Additional Information

Details:

Proponent Information:

Non Fed proposal summary before submitting to FAA.

For proponent new FCR request which obtain FAA concurrence as a project, the PIM typically works with FAA NFDC to request the FAA Facility Identification Code or IDENT.

Upon approval of the FCR request, the PIM user is requested to enter the FAA NFDC IDENT prior to selecting the 'Submit to FAA Spectrum' function. Once approved, the FAA status of the assignment will be updated to RN. The cancel button may be used to close this window.